

DMX-R 80/DTX-R 80

STANDARD EQUIPMENT



Equipped with:

- IP 55 silenced turbine motor
- Stainless steel container
- Mechanical horizontal & simple manual filter cleaning system
- Steel closing hooks
- Static electric shock inhibitor
- Power coated steel structure and containers
- Steering wheels with brake.
- Liquid float valve
- Pressure relief valve, safety device avoiding engine problems in case of clogging
- Drain hose system
- Quick release tank system

- Flexible hose \varnothing 40 - 3 m
code 5.209.0159



- Flat lance \varnothing 40
code 3.754.0048



- Cloth filter
code 5.509.0039



Optional:

- Washable filter
5.212.0021



- Kit 6.205.0115

- Steel curve + pipe
 \varnothing 40



- Round brush \varnothing 40



400 mm

- Accessories holder \varnothing 40



- Floor Brush



- Wet tool



- Carpet tool



	DMX-R 80 1-22	DTX-R 80 1-30
code	8.265.0001	8.265.0002
abs. power W	2200	3000
n°/type motor	1/induction	1/induction
max vacuum (actual)	21/25 kPa (2100/2500 mm H ₂ O)	25/32 kPa (2500/3200 mm H ₂ O)
max Airflow	97 l/s	97 l/s
container capacity	80 l.	80 l.
noise level	74 dB(A)	74 dB(A)
voltage	230 V~50 Hz (1Ph)	400 V~50 Hz (3Ph)
inlet \varnothing - type (s=straight; t=tangential)	40 mm - s	40 mm - s
filtering capacity/surface	5 μ m/ 4300 cm ²	5 μ m/ 4300 cm ²
cable lenght	10 m	10 m
dimensions/weight	47x71x115 cm/70 Kg	47x71x115 cm/70 Kg