INDUSTRIAL

# DTX100 1-26 SM Ex 2-22











### **Equipped with:**

- 1 single stage side channel blower with three-phase induction motor
- AISI 304 non-magnetic stainless steel container (with side inlet channel) & filter chamber.
- Power coated steel structure.
- Mechanical horizontal & simple manual filter cleaning system
- Antistatic polyester non woven fabric pockets filter, class M
- Wheeled AISI 304 s.s. container with inbuilt quick release handle, drain plug and full load level
- Trolley with front pivoting non-marking wheels (with breake) & large inbuilt accessories basket
- Removable motors unit header through metal hooks

## STANDARD EQUIPMENT

0.144.0117 Antistatic Polyester pockets filter 2 m², class M

0.144.0008 Quick release adaptor Ø 60-50 (1x) There isn't any hose or tool provided within the unit.

Optional minimum set to run the unit:

6.205.0049 3 m complete EVA Ø 50 hose set (1x)

#### Optional:

Longopack set
0.144.0110 Hopper for spool bag collection
0.144.0111 Tray for spool bag collection
0.144.0112 Longopack 22m bag spools (box
of 4)

#### **Filters**

0.144.0118 Antistatic Polyester pockets filter 3m², class M

0.144.0119 180°C Heatproof polyester pockets filter 2m², class M

0.144.0120 Flat cartridge Hepa secondary filter assembly kit 0.144.0121 Flat cartridge Hepa filter

0.144.0121 Flat cartridge Hepa filte (replacement)

## Wet operations

0.144.0045 Galvanized floater support (without floater)

0.144.0046 Floater for wet suction 0.144.0122 Wet filter protection cone for floater stop

0.144.0113 Container discharge faucet kit

#### **Metal chips separations**

0.144.0123 Galvanized chip basket including floater

0.144.0122 Wet filter protection cone for floater stop

	DTX100 1-26 SM Ex 2-22
code	0.045.0303
abs. power W	2600
n°/type motor	1/induction
max vacuum (actual)	32 kPa (26 kPa)
max Airflow	320 m³/h - 89 l/s
container capacity	100
noise level	78 dB(A)
voltage	400 V~50 Hz (3Ph)
inlet $\varnothing$ - type (s=straight; t=tangential)	60 mm - t
filtering capacity/surface	2 μm - 99,9% (M Class)/ 20000 cm <sup>2</sup>
cable lenght	10 m
dimensions/weight	80x60x171 cm / 102kg - 225 lb