

SMX-R 80













CHARACTERISTICS

• 3 silenced two stage by-pass cooling motors • Stainless steel container • Mechanical horizontal and simple manual filter cleaning system • Steel closing hooks • Static electric shock inhibitor • Power coated steel structure • Trolley with front pivoting non-marking wheels (with breake) & large inbuilt accessories basket • Liquid float valve. • Drain System

TECHNICAL DATA

| | SMX-R 80 3-36S DS |
|---|----------------------------|
| code | 40033-00003 |
| abs. power W | 3000 |
| n°/type motor | 3 x two stages universal |
| max vacuum (actual) | 24 kPa (2400 mmH2O) |
| max Airflow | 162 l/s |
| container capacity | 80 |
| noise level | 76 dB(A) |
| voltage | 220-240 V~50-60 Hz (1Ph) |
| inlet Ø - type (s=straight; t=tangential) | 70 mm - s |
| filtering capacity/surface | 5 μm/ 4460 cm ² |
| cable lenght | 7,5 m |
| dimension (cm)/weight | 68x58x130/45Kg |

INDUSTRIAL

PLUS



3 double stage silenced motors, suction system with by-pass cooling, liquid float valve and antistatic device



80 litres stainless steel tank



Cloth filter and manual filter shaker that keeps the filter clean thanks to a simple manual swing mechanism



Power coated steel structure with front pivoting non-marking wheels with brakes and large inbuilt storage compartment

STANDARD EQUIPMENT



• 00070-00679 - Cloth filter

• 00014-02300 Quick release adaptor Ø70-50 (1x)

There isn't any hose or tool provided within the unit.

OPTIONAL

• 10001-09534 KIT 1 for industrial cleaning, included:

• 00014-02293 2 x Accessories sleeve eva Ø 50 • 00080-01831 4 x Eva conductive flexible hose Ø 50 (mt 4) • 00026-01129 Steel handle Ø50 • 00080-04097 Dust inox tool • 00080-01589 PVC flat lance with galvanized joint Ø50 • 00080-01590 PVC round brush with galvanized joint Ø50

• 10001-09535 KIT 2 for oil and swarf cleaning, included:

• 00014-02292 2 x Accessories sleeve PUR/PVC Ø 50 • 00080-01833 4 x Pur antistatic flexible hose Ø 50 (mt 4) • 00040-01251 Galvanized chip basket • 00080-01587 Rubber antistatic round lance Ø50

| Optional minimum set to run the unit: | | |
|---|--|--|
| • 10001-09372 3m complete EVA Ø50 hose set (1x) + 00080-01589 adapter | | |