WET & DRY



Domus IR











CHARACTERISTICS

• 2 silenced two stage motor. • Suction system with by-pass cooling. • Stainless steel tank. • Professional closing hooks. • Static electric shock inhibitor. • Tilting tank. • Fully removable tank. • Shock proof trolley. • Liquid float valve. • Cloth filter. • 10 m power cable. • Easy standing head (during filter cleaning). • Cable holder. • Traceless wheels. • Accessories Ø 40.

TECHNICAL DATA

	Domus IR
code	40005-00001
voltage	220-240V ~ 50-60Hz
n°motors - power (max)	2 - 2000 (2400) W silenced two stage motor
column depression	22 kPa/2240 mmH ₂ O
air suction	108 l/s
total volume/dust/liquid	78 l./35 l./48 l.
dimension (cm)/weight	62x51x99/32 kg

LAVOR

PLUS



Anti-tipping head support, very useful while filter cleaning or when opening the tank for emptying



Shock proof trolley with two front pivoting wheels and two big rear wheels for better stability and easy movement



Antistatic device eliminating those annoying magnetic fields that can form inside the tank due to the high speed movement of particles. Improves user's comfort of use



Tilting anti-corrosion stainless steel tank for easy emptying and fully removable tank if necessary

STANDARD EQUIPMENT

• 00080-03979 Hose 2,5 m	• 10001-09446	• 00080-01931	• 00080-01932	• 00080-01956
• 00080-01957	• 00080-01958	• 00070-00679 Cloth filter		

OPTIONAL

• 10001-08169 Paper collector filter set (10 pcs) • 10001-09545 Cloth filter dust	• 10001-08208 Nylon filter	• 10001-08168 Washable filter	• 10001-08178 Hepa filter
--	----------------------------	-------------------------------	---------------------------