

Taurus IR 2 Way



Equipped with:

- 3 silenced two stage motor.
- S. S. tank.
- Professional closing hooks.
- Static electric shock inhibitor.
- Suction system with by-pass cooling.
- Tilting tank.
- Fully removable tank.
- Shock proof trolley.
- Liquid float valve.
- Cloth filter.
- 10 m power cable.
- Easy standing head (during filter cleaning).
- Cable holder.
- Traceless wheels.
- Accessories Ø 40.

- Hose connection for second operator



STANDARD EQUIPMENT

- 2 x 5.209.0082
Hose 5 m




- 2 x 3.754.0048



- 2 x 3.754.0049



- 5.509.0039
Cloth filter



Optional:

- 6.205.0126 - Ø 40 chromium plated steel curve and extension pipe kit
- 6.205.0121 - Ø 40 complete accessories kit (holder accessories, floor brush, wet tool, carpet tool)
- 5.212.0093 Cloth filter for fine dust.

Taurus IR 2 Way	
code	8.212.0523
voltage	220-240V ~ 50-60Hz
n°motors - power (max)	3 - 3000 (3600) W silenced two stage motor
column depression	22 kPa/2240 mmH ₂ O
air suction	162 l/s
total volume/dust/liquid	78 l./35 l./48 l.
dimension/weight	62x51x99 cm / 33 kg