WET & DRY



# Taurus IR 2 Way











### **CHARACTERISTICS**

• 3 silenced two stage motor. • Stainless steel tank. • Professional closing hooks. • Static electric shock inhibitor. • Suction system with bypass cooling. • Tilting tank. • Fully removable tank. • Shock proof trolley. • Liquid float valve. • Cloth filter. • 10 m power cable. • Easy standing head (during filter cleaning). • Cable holder. • Traceless wheels. • Accessories Ø 40.

### **TECHNICAL DATA**

	Taurus IR 2 Way
code	40004-00023
voltage	220-240V ~ 50-60Hz
n°motors - power (max)	3 - 3000 (3600) W silenced two stage motor
column depression	22 kPa/2240 mmH <sub>2</sub> O
air suction	162 l/s
total volume/dust/liquid	78 l./35 l./48 l.
dimension (cm)/weight	62x51x99 /33 kg

WET & DRY

### **PLUS**



Anti-tipping head support, very useful while filter cleaning or when opening the tank for emptying



Shock proof trolley with two front pivoting wheels and two big rear wheels for better stability and easy movement



Additional hose connection to allow two operators to work simultaneously



Tilting anti-corrosion stainless steel tank for easy emptying and fully removable tank if necessary

### **STANDARD EQUIPMENT**



• 2 x 00080-03990 Hose 5 m







# **OPTIONAL**

• 10001-09446 - Ø 40 chromium | • 10001-09441 - Ø 40 complete plated steel curve and extension pipe kit

accessories kit (holder accessories, floor brush, wet tool, carpet tool)

• 10001-08208 Cloth filter for fine dust.