










Windy 165 PF



DOTATION DE SÉRIE

- 5.209.0021 Flexible 2,5 m 
- 6.205.0126 
- 3.754.0048 
- 3.754.0049 
- 3.754.0185  300 mm
- 3.754.0169 
- 3.754.0170 
- 3.752.0175 
- 6.205.0151 

En option:

- 5.212.0022 Kit 10 filtres sacs papier
 - 5.212.0094 Filtre nylon
 - 5.212.0157 Cartouche filtrante
 - 5.212.0158 HEPA filtre
 - 5.212.0155 Filtre lavable

Equipé avec:

- 1 moteur en by-pass à rendement élevé • Système d'aspiration avec refroidissement par by-pass • Cuve en plastique (PP) • Chariot anti choc • Clapet flottant pour liquide
- Filtre textile • Câble d'alimentation 7,5 m • Porte accessoires inclus. • Roues pour zone alimentaires • Accessoires Ø 40.

Windy 165 PF	
Référence	8.263.0002
Tension	220-240V ~ 50-60Hz
N° de moteurs - Puissance (max)	1 - 1200 (1400) W
Dépression	24 kPa/2400 mmH ₂ O
Débit air	65 l/s
Volume total/pouss./liquide	65 l./30 l./40 l.
Dimensions/poids	44x46x96 cm/11 kg