


## Windy 365 IR



### Equipped with:

- 3 high efficiency by pass motors.
- Suction system with by-pass cooling.
- Filter cleaning system.
- S. S. tank.
- Static electric shock inhibitor.
- Tilting tank.
- Fully removable tank.
- Shock proof trolley.
- Liquid float valve.
- Cloth filter.
- 7,5 m power cable.
- Traceless wheels.
- Accessories Ø 40.
- Handy accessory holder.

### STANDARD EQUIPMENT

• 5.209.0021 Hose 2,5 m	
• 6.205.0126	
• 3.754.0048	
• 3.754.0049	
• 3.754.0083 400 mm	
• 3.754.0084	
• 3.754.0085	
• 6.205.0151 Cloth filter	

### Optional:

- 5.212.0022 Paper collector filter set - 10 pcs
- 5.209.0177 Cloth filter for fine dust
- 5.212.0093 Nylon filter

Windy 365 IR	
code	8.240.0001
voltage	220-240V ~ 50-60Hz
n°motors - power (max)	3 - 3000 (3600) W
column depression	22 kPa/2200 mmH <sub>2</sub> O
air suction	195 l/s
total volume/dust/liquid	65 l./30 l./40 l.
dimension/weight	62x51x100 cm/20 kg