WET & DRY



Windy 378 PF













CHARACTERISTICS

• 3 high efficiency by pass motors. • Suction system with by-pass cooling. • Filter cleaning system. • Plastic tank (PP). • Shock proof trolley. • Liquid float valve. • Static electric shock inhibitor. • Drain hose system. • 7,5 m power cable. • Traceless wheels. • Accessories Ø 40. • Handy accessory holder. • Pneumatic filter shaker

TECHNICAL DATA

	Windy 378 PF
code	40021-00006
voltage	220-240V ~ 50-60Hz
n°motors - power (max)	3 - 3000 (3600) W High efficiency motor.
column depression	22 kPα/2200 mmH ₂ O
air suction	195 l/s
total volume/dust/liquid	78 l./35 l./48 l.
dimension (cm)/weight	62x51x99/23,5 kg

LAVOR

PLUS



3 high efficiency motors, suction system with by-pass cooling, rotating ON/OFF main switch



Pneumatic filter shaker and flow reverse for perfect filter cleaning for top vacuum performances



Drain hose system for tank easy emptying



Shock proof trolley with pivoting wheels for easy movement and base with accessory storage facility (accessories d. 40 mm)

STANDARD EQUIPMENT

• 00080-03979 Hose 2,5 m	• 10001-09446	• 00080-01931	• 00080-01932	• 00080-01956
• 00080-01957	• 00080-01958	• 10001-09544 Cloth filter		

OPTIONAL

• 10001-08169 Paper collector filter set (10 pcs)	• 10001-09545 Cloth filter for fine dust	• 10001-08208 Nylon filter	• 10001-08168 Washable filter	• 10001-08178 Hepa filter
---	--	----------------------------	-------------------------------	---------------------------