SPRAY EXTRACTION UNITS



Costellation IR











CHARACTERISTICS

• 2 silenced two stage motor. • Suction system with by-pass cooling. • Stainless steel tank. • Detergent pump (2x48W – 0,7-1,2 l/m – 5 bar). • Professional closing hooks. • Static electric shock inhibitor. • Tilting tank. • Fully removable tank. • 11 l. detergent tank. • Shock proof trolley. • Liquid float valve. • Cloth filter. • 10 m power cable. • Easy standing head (during filter cleaning). • Traceless wheels. • Accessories Ø 40.

TECHNICAL DATA

| | Costellation IR |
|--------------------------|--|
| code | 40011-00008 |
| voltage | 220-240V ~ 50Hz |
| n°motors - power (max) | 2 - 2200 (2400) W silenced two stage motor |
| column depression | 22 kPα/2240 mmH ₂ O |
| air suction | 108 l/s |
| total volume/dust/liquid | 78 l./35 l./48 l. |
| dimension (cm)/weight | 62x51x99/35,5 kg |

SPRAY EXTRACTION UNITS

PLUS



2 double stage motors, suction system with by-pass cooling, float valve and antistatic device



2 detergent pumps 48W - 0,7/1,2 l/m - 5 bar



Shock proof trolley with two front pivoting wheels and two big rear wheels for better stability and easy movement, 11 l detergent solution tank and 78 l stainless steel tank



Tilting anti-corrosion stainless steel tank for easy emptying and fully removable tank if necessary

STANDARD EQUIPMENT



• 10001-09449 Hose 2,5 m



• 10001-09452



• 00080-03052



• 00070-00679 Cloth filter

OPTIONAL

• 10001-09545 Cloth filter for fine dust

• 10001-08208 Nylon filter

• 10001-08168

Washable filter

• 10001-08178 HEPA filter