SPRAY EXTRACTION UNITS

LAVOR

Solaris IF











CHARACTERISTICS

• Silenced two stage motor. • Suction system with by-pass cooling. • Stainless steel tank. • Detergent pump (2x48W – 1 l/m – 7 bar). • Professional closing hooks. • Static electric shock inhibitor. • Drain hose system. • 25 l. detergent tank. • Shock proof trolley. • Liquid float valve. • Cloth filter. • 10 m power cable. • Easy standing head (during filter cleaning). • Traceless wheels. • Accessories Ø 40.

TECHNICAL DATA

	Solaris IF
code	40011-00002
voltage	220-230V ~ 50Hz
n°motors - power (max)	2 - 2200 (2400) W silenced two stage motor
column depression	22 kPα/2240 mmH ₂ O
air suction	108 l/s
total volume/dust/liquid	78 l./35 l./48 l.
dimension (cm)/weight	62x51x96/33 kg

SPRAY EXTRACTION UNITS

PLUS



2 double stage motors, suction system with by-pass cooling, float valve and antistatic device



2 detergent pumps 48W - 1 l/m - 7 bar



Shock proof trolley with two front pivoting wheels and two big rear wheels for better stability and easy movement, 25 I detergent solution tank and 78 l stainless steel tank



Drain hose system for tank easy emptying

STANDARD EQUIPMENT



• 10001-09449 Hose 2,5 m



• 10001-09452





• 00070-00679 Cloth filter

OPTIONAL

• 10001-08169 Paper collector • 10001-09545 Cloth filter for • 10001-08168 • 10001-08208 Nylon filter • 10001-08178 HEPA filter filter set (10 pcs) fine dust Washable filter