


GV Egon VAC 4.1 Plus



MORE INFO



CHARACTERISTICS

• ABS body • Ready steam warning lamp • Boiler 1,9 kW Stainless steel AISI 304 • Low level water lamp indicator • Boiler is refilled continuously • Flex hose 2 m • Wheels suitable for use in food processing area • ON/OFF main switch with indicator lamp • ON/OFF boiler switch with indicator lamp • Steam regulation • Recovery tank capacity 8 l. • Washable filter • HEPA filtering system H14 cod. 00070-00605 • Pressure gauge. • Suction speed control (4 level) on handle

TECHNICAL DATA

	GV Egon VAC 4.1 Plus
code	45002-00003
max steam pressure/temperature	5 bar/152° C
boiler absorbed power	1900 W/220-240V ~ 50/60Hz (Ph 1)
vacuum motor absorbed power	1200 (max 1400) W
column depression/air flow	24 kPa/220 m ³ /h
recovery tank capacity	8 l
dimension (cm)/weight	55x40x35/14,3 kg

PLUS



User friendly control panel with ON/OFF main switch and steam ready light. Equipped with stainless steel boiler with unlimited autonomy, ready in a few minutes



Egon Vac 4.1 is equipped with an HEPA H14 filter which remove the 99.995% of the air contaminants preventing the spread of bacterial and viral organism present in the air.

























Steam regulation directly from the gun



Fully removable recovery tank for easy emptying and perfect tank cleaning

STANDARD EQUIPMENT

 • 10002-06232	 • 2 X 00080-01883	 • 00080-02052	 • 00071-02658	 • 00071-02659
 • 00071-02660	 • 00080-03750 PEK	 • 00080-03752 Stainless steel	 • 00080-03751 Brass	 • 00080-02911
 • 00080-02061	 • 00071-02668	 • 00071-02669	 • 00080-01912	 • 10001-08349
 • 00080-01980	 • 00080-04382	 • 00080-02077	 • 10001-10694	 • 00080-02076
 • 00009-02541	 • 00080-03121			