

## Thermic 10.1 HW Hot water self-contained unit

**T.V.** Thermal Valve



**NEW**



### Equipped with:

- Sturdy frame with rubber feet, bar for vertical lift
- Professional hot water high pressure cleaner for uses without connection to electricity grid
- Yanmar L100V Diesel engine (air cooled)
- Electrical starting-up, battery included
- No engine-oil safety device (oil-alert)
- Automatic decelerator to reduce RPM in by-pass mode
- 1560 RPM reducer between engine and pump.
- Self-priming CL5 Lavor pump, 3 ceramic pistons, brass pump head and unloader valve flanged
- Fuel tank with level float and fill up filter
- Double coil vertical stainless steel high efficiency boiler with stainless steel outer casing
- Electronic temperature setting system with constant water temperature
- PED 2014/68/CE cat. II certification for steam operations
- Flow-switch operated burner
- Safety valve
- Boiler thermal protection
- Flame control kit

### STANDARD EQUIPMENT

- 0.966.0083 Gun M22 - 3/8 with rotating coupling.



- 0.966.0084 Lance M22 high/low pressure



- 3.103.0113 nozzle 25° type 060



- 0.966.0086 High pressure hose 10 m



- Flame control kit



- RPM decelerator kit



### Optional:

- 0.966.0110 ROTOX lance 255 bar
- 4.618.0012 Extension hose 10 m
- 4.618.0057 Extension hose 20 m
- Sand blasting lance (on request)
  - 3.555.1233 Wheel kit
- 3.555.1234 Soundproofing kit (on request)
- 0.966.0109 Hose reel with hose 20m

	Thermic 10.1 HW
code	0.066.0062
operat. pressure	170 bar-2465 psi
delivery rate	1020 l/h-4.4 GPM
engine type/HP	Yanmar L100V/10
motorpump type/RPM	CL5/1560
max. water inlet/outlet temp.	60/140 °C
dimension/weight	120x73x95cm / 200 Kg - 440 lbs