

Darwin Pro**CHARACTERISTICS**

- Boiler ventilation unit built-on motorpump (energy saving)
- Three ceramic coated pistons, brass linear pump head with built-in by-pass valve with double gasket
- Suction and delivery stainless steel valves
- Vertical burner with high thermal efficiency steel coil
- Temperature regulation gauge
- Pivoting wheel with brake
- Diesel pump with discharge by-pass valve
- Detergent built-in tank (3,5 lt) for indirect suction
- Possibility to integrated detergent suction with external probe
- Diesel tank capacity (15 lt)
- Glycerine pressure gauge
- Metal lance
- Accessory holder
- Ergonomic handle
- Integrated hose reel with 10m hp hose (only code 36093-00018)

TECHNICAL DATA

	Darwin Pro 1310 LP	Darwin Pro 1310 LP
code	36093-00017	36093-00018
rated/max pressure	135/150 bar - 1958/2175 psi	135/150 bar - 1958/2175 psi
max delivery flow rate	600 l/h - 2.64 gpm	600 l/h - 2.64 gpm
abs. power/supply	3000 W/230V 1~50Hz	3000 W/230V 1~50Hz
motor power	2,0 kW	2,0 kW
pump model	CL3.1/2800 rpm	CL3.1/2800 rpm
T max water inlet/outlet	40/90 °C	40/ 90°C
dimension (cm)/weight	85x56x86/80 Kg (176 lbs)	85x56x86/82 Kg (180 lbs)

PLUS

Handy pressure connected hose reel to use only the necessary length of hose and to easily rewind it after use (36093-00018 model)



Shockproof front and rear protective bar, ideal for manual lifting



Integral ceramic self-priming three-piston linear pump, the best solution for a professional product



Cleaning tank with suction quantity adjustment system, possibility of suction from external tank

STANDARD EQUIPMENT

• 00080-01701 Gun M22 - 3/8 with rotating coupling	• 00080-04943 Lance M22 high/low pressure	• 00080-03186 Nozzle type 035	• 00080-02254 High pressure hose 8 m (mod. 36093-00017) • 00080-04434 High pressure hose 10 m (mod. 36093-00018)	• Storage bag (mod. 36093-00017)