


**Darwin**

**T.S.** Total Stop

**2800**  
RPM

**NEW**



MPBX1

**STANDARD EQUIPMENT**

- 3.700.0036 Gun M22 - 3/8"



- 3.701.0015 Lance M22 high/low pressure



- 3.103.0047 Nozzle 15030



- 4.618.0049 High pressure hose 8 m (on cod. 8.675.0001)
- 4.618.0248 High pressure hose 10 m (on cod. 8.675.0002)



- Power cable 5 m



- Storage bag (on cod. 8.675.0001)

**Equipped with:**

- Boiler ventilation unit built-on motorpump (energy saving)
- Three ceramic coated pistons, brass axial pump head with built-in by-pass valve with double gasket
- Suction and delivery S. S. valves
- Vertical burner with high thermal efficiency steel coil
- Temperature regulation gauge
- Pivoting wheel with brake
- Diesel pump with discharge by-pass valve
- Detergent built-in tank (3,5 lt) for indirect suction
- Possibility to integrated detergent suction with external probe
- Diesel tank capacity (15 lt)
- Glycerine pressure gauge
- Metal lance
- Accessory holder
- Ergonomic handle
- Integrated hose reel with 10m H.P hose (only model Plus code 8.675.0002)

	Darwin 1310 XP	Darwin Plus 1310 XP
code	8.675.0001	8.675.0002
operat. pressure/max	130/150 bar-1885/2175 psi	130/150 bar-1885/2175 psi
delivery rate	600 l/h - 2.64 GPM	600 l/h - 2.64 GPM
abs. power/voltage	3000W-230V~50Hz 1 ph	3000W-230V~50Hz 1 ph
pump type/RPM	MPBX1 / 2800	MPBX1 / 2800
max. water inlet/outlet temp.	40/90 °C	40/90 °C
dimension/weight	80x55x100 cm / 80 Kg - 176 lbs	80x55x100 cm / 82 Kg - 180 lbs