

**HHPV**



**Motor with elastic joint**

Only mod. 2015 - 2021

**NEW**



**CL3.8/CL6.0**

**STANDARD EQUIPMENT**

- 3.700.0030 Gun M22 - 3/8" with rotating coupling



- 3.708.0001 Lance M22 high/low pressure



- 3.103.0050 Nozzle type 15045 (mod. 2015)
- 3.103.0055 Nozzle type 1507 (mod. 2021)
- 3.103.0050 Nozzle type 15045 (mod. 1212)



- 4.618.0143 High pressure hose 10 m



- Power cable 5 m.

**Optional:**

- 4.618.0057 Extension hose 20m (mod. 2015 LP)
- 3.555.1588 Extension hose 20m + 3.555.0355 Coupling (mod. 2021 LP)
- 4.618.0057 Extension hose 20m (mod. 1212 LP)

- Anti scale device (on request)
- Rotating booms (on request)

- Models with hose reel (20mt H.P. hose included):

- 8.624.0646 HHPV 1212LP
- 8.624.0644 HHPV 2015LP
- 8.624.0648 HHPV 2021LP



**Equipped with:**

- 4-pole electric motor (1450 RPM) with thermal protection
- Integrated flexible coupling, for a better pump/motor coupling (mod 2015-2021)
- CL3.8 / CL6.0 pumps with brass head and three ceramic pistons
- Professional unloader valve with external by-pass
- Suction and delivery valves in stainless steel
- Low voltage delayed Total Stop
- High pressure detergent suction with solenoid valve
- 25 liter Diesel tank with level indicator and filter
- Vertical boiler with high thermal efficiency steel coil
- Control panel with protective cover
- General shutdown (when the machine is not used for a long time)
- Anti-limescale device with pump and tank (1 l)
- Microleak detector
- Accessory holder
- Burner activated by flow switch and pressure switch
- Internal insulating protection to resist high/low temperatures
- Antifreeze resistance
- Internal water tank with float level
- Flame control
- Stainless steel HHPX (on request)

|                               | HHPV 1212 LP                   | HHPV 2015 LP                   | HHPV 2021 LP                   |
|-------------------------------|--------------------------------|--------------------------------|--------------------------------|
| code                          | 8.624.0647                     | 8.624.0645                     | 8.624.0649                     |
| operat. pressure              | 110 bar-1595 psi               | 200 bar-2900 psi               | 200 bar-2900 psi               |
| delivery rate                 | 720 l/h-3.1 GPM                | 900 l/h-3.96 GPM               | 1260 l/h-5.55 GPM              |
| abs. power/voltage            | 3000W - 230V~50Hz 1ph          | 7300W - 400V~50Hz 3ph          | 9700W - 400V~50Hz 3 ph         |
| motor/pump type/RPM           | CL3.8/1450 RPM                 | CL6.0/1450 RPM                 | CL6.0/1450 RPM                 |
| max. water inlet/outlet temp. | 60/110 °C                      | 60/110 °C                      | 60/110 °C                      |
| dimension/weight              | 76x48x180cm / 190 Kg - 418 lbs | 76x48x180cm / 200 Kg - 440 lbs | 76x48x180cm / 210 Kg - 462 lbs |