


Kansas 2.0

ZERO EMISSION

High efficiency **SILENT**

NEW



CHARACTERISTICS

- **18/24/36 kW 70 lt electric boiler** • 4-pole electric motor (1400 rpm) with thermal protection, air cooling • Three ceramic pistons, brass linear pump head • Stainless steel suction and delivery valves and hot water gaskets • Professional nickel-plated drain valve suitable for hot water • Low voltage and delayed Total Stop • Detergent flow with integrated 22 litre detergent tank with injector (low pressure) • Non-marking wheels • Safety valve • Anti-scale device, with integrated 22 litre tank • Panel with analogue controls • Hose reel (optional) • General shutdown in case of prolonged machine non-use
- Micro-leak detection system

TECHNICAL DATA

	Kansas 2.0 1510 LP	Kansas 2.0 1512 LP	Kansas 2.0 1710 LP	Kansas 2.0 1912 LP
code	36137-00004	36137-00005	36137-00006	36137-00007
rated/max pressure	150/180 bar - 2175/2610 psi	150/180 bar - 2175/2610 psi	170/190 bar - 2465/2755 psi	190/210 bar - 2755/3045 psi
max delivery flow rate	600 l/h - 2.6 gpm	720 l/h - 3.1 gpm	600 l/h - 2.6 gpm	720 l/h - 3.1 gpm
abs. power/supply	21000 W/400V 3~50Hz	28000 W/400V 3~50Hz	28000 W/400V 3~50Hz	41000 W/400V 3~50Hz
heating power	18 kW	24 kW	24 kW	36 kW
pump model	MPCL3.8/1400 rpm	MPCL3.8/1400 rpm	MPCL3.8/1400 rpm	MPCL3.8/1400 rpm
T max water inlet/outlet	60/85 °C	60/85 °C	60/85 °C	60/85 °C
dimension (cm)/weight	125x69x87/150 Kg (330 lbs)	125x69x87/150 Kg - 330 lbs	125x69x87/150 Kg - 330 lbs	125x69x87/150 Kg - 330 lbs

PLUS



Professional motor pump with 4-pole motor (1400 rpm) and self-priming linear pump with three pistons in integral ceramic, double oil viewer, brass head and water seals for operation up to 85°C



Electric boiler heating power 18/24/36 kW, effective volume 70 litres







Large 22-litre detergent and anti-scale tanks



Large-diameter front and pivoting rear wheels for stable positioning and to facilitate movement on any type of surface

STANDARD EQUIPMENT

 <ul style="list-style-type: none"> • 00080-01695 Gun M22 - 3/8" with rotating coupling. 	 <ul style="list-style-type: none"> • 10002-04732 Lance M22 high pressure. 	 <ul style="list-style-type: none"> • 00080-03230 Nozzle type 030 (mod. 1510) • 00080-03220 Nozzle type 045 (mod. 1512) • 00080-00355 Nozzle type 028 (mod. 1710) • 00080-00354 Nozzle type 040 (mod. 1912) 	 <ul style="list-style-type: none"> • 00080-02263 High pressure hose food industry 10 m 	
--	--	--	---	--

OPTIONAL

<ul style="list-style-type: none"> • 10001-10198 - Hose reel with brake (hose not included) 	<ul style="list-style-type: none"> • 00073-00114 - Antiscale LC-PRECAL (pz. 4 x 5 lt.) 	<ul style="list-style-type: none"> • Turbo Lance code: 00080-02966 - (mod. 1512/1912) 00080-02986 - (mod. 1510/1710) 		
--	---	---	--	--