

Texas-R



STANDARD EQUIPMENT

- 3.700.0030 Gun M22 - 3/8" with rotating coupling.



- 3.701.0015 Lance M22 high/low pressure



- 3.103.0050 Nozzle type 045 (mod. 1211 LP)
- 3.103.0048 Nozzle type 035 (mod. 1611 LP)



- 4.618.0049 High pressure hose 8 m (mod 1211 LP)
- 4.618.0143 High pressure hose 10 m (mod 1611 LP)



- Power cable 5 m

Optional:

- 6.608.0073 Hose reel with brake (hose not included)

Equipped with:

- 4 poles electrical motor (1450 RPM) with thermal protection.
- Three ceramic coated pistons (1 ph), full ceramic pistons (3 ph), brass linear pump head with built-in by-pass valve.
- Low voltage and delayed Total Stop.
- Suction and delivery S. S. valves.
- Vertical burner with high thermal efficiency steel coil.
- Temperature regulation gauge with high sensitive stainless steel sensor.
- Detergent built-in tank (4,2 lt) for indirect suction.
- Auxiliary motor for burner.
- Hose reel with brake **(optional)**.

	Texas-R 1211 LP	Texas-R 1611 LP
code	8.630.0101	8.630.0103
operat. pressure/max	120/150 bar-1740/2175 psi	160 bar-2320 psi
delivery rate	660 l/h-2.91 GPM	660 l/h-2.91 GPM
abs. power/voltage	3000W - 230V~50Hz 1ph	4300W - 400V~50Hz 3 ph
motor/pump type/RPM	MP3/1450 RPM	MP3.5/1450 RPM
max. water inlet/outlet temp.	40/110 °C	40/110 °C
dimension/weight	85x65x97 cm/112 Kg - 246 lbs	85x65x97 cm/128 Kg - 282 lbs