

Texas-R











CHARACTERISTICS

- 4 poles electrical motor (1400 rpm) with thermal protection. Three ceramic coated pistons (1 ph), full ceramic pistons (3 ph), brass linear pump head with built-in by-pass valve. Low voltage and delayed Total Stop. Suction and delivery Stainless steel valves. Vertical burner with high thermal efficiency steel coil.
- Temperature regulation gauge with high sensitive stainless steel sensor. Detergent built-in tank (4,2 lt) for indirect suction. Auxiliary motor for burner.
- Hose reel with brake (optional).

TECHNICAL DATA

	Texas-R 1211 LP	Texas-R 1611 LP
code	36080-00002	36080-00004
rated/max pressure	120/150 bar - 1740/2175 psi	160/180 bar - 2320/2610 psi
max delivery flow rate	660 l/h - 2.91 gpm	660 l/h - 2.91 gpm
abs. power/supply	3000 W/230V 1~50Hz	4300 W/400V 3~50Hz
motor power	2,2 kW	4,0 kW
pump model	MP3/1400 rpm	MP3.5/1400 rpm
T max water inlet/outlet	40/110 °C	40/110 °C
dimension (cm)/weight	85x65x97/112 Kg (246 lbs)	85x65x97/128 Kg (282 lbs)

HOT WATER

PLUS



Side supports for gun and lance housing



Sturdy large diameter wheels for stability and ease of movement



Professional motor pump with 4-pole motor (1400 rpm) and self-priming linear pump: the low rotation speed significantly extends the life of the components inside the motor pump, guaranteeing greater efficiency and silence



Diesel oil level sensor with fuel shortage indicator light

STANDARD EQUIPMENT



with rotating coupling



high/low pressure



- 00080-03188 Nozzle type 045 (mod. 1211)
- 00080-03186 Nozzle type 035 (mod. 1611)



- 00080-02254 High pressure hose 8 m (mod. 1211)
- 00080-02347 High pressure hose 10 m (mod. 1611)

OPTIONAL

• 10001-10254 Hose reel with brake (hose not included)

• High pressure hose code: 00080-02254 8 m - 210 bar (mod. 1211) 00080-02258 10 m - 310 bar 00080-02261 20 m - 400 bar 00080-02264 10 m R2

• Turbo Lance code: 00080-02966 00080-02981

• 00080-02957 Sandblasting lance