

Thermic 10.1 D

T.V. Thermal Valve



CRANKSHAFT



NEW

SELF PRIMING PUMP



CL6.0

STANDARD EQUIPMENT

- 3.700.0030 Gun M22



- 0.966.0084 Lance M22 high/low pressure.



- 3.103.0208 Nozzle 075 (mod.1621)
- 3.103.0111 Nozzle 050 (mod.2016)



- 0.966.0086 High pressure hose R2 10 m (mod.2016)
- 0.966.0011 High pressure hose R2 10 m (mod.1621)



Optional:

- 5.012.0319 Suction hose with check valve



- 0.966.0114 ROTOX lance 255 bar 050 (mod.2016)
- 0.966.0115 ROTOX lance 255 bar 070 (mod.1621)
- 6.602.0028 Sand blasting lance
- 0.966.0111 Kit hose reel with 15m R2 3/8" hose



Equipped with:

- Three ceramic pistons, brass linear pump head with built-in by-pass valve.
- 1560 RPM gear box between engine and pump.
- By-pass with thermostatic valve.
- Automatic RPM regulation.
- Electrical start with engine functions control.
- Yanmar L100V Diesel engine (air cooled) with integrated Diesel tank.
- Integrated regulable detergent suction with external suction probe.
- Pressure regulator.
- Glycerine pressure gauge.
- Suction hose with check valve **(optional)**.
- Heavy duty steel frame.
- Battery included.
- Brass filter.
- Pneumatic effect Ø 260 wheels with brake

	Thermic 10.1 D 1621	Thermic 10.1 D 2016
code	0.066.0085	0.066.0084
operat. pressure	160 bar-2320 psi	200 bar-2900 psi
delivery rate	1260 l/h-5.5 GPM	960 l/h-4.2 GPM
engine type/hp	Yanmar L100V/9,3	Yanmar L100V/9,3
pump type/RPM	CL6.0/1560 RPM	CL6.0/1560 RPM
max. water inlet temp.	60 °C	60 °C
dimension/weight	95x68x95cm / 124 Kg - 231 lbs	95x68x95cm / 124 Kg - 231 lbs