

Thermic 10 D

T.V. Thermal Valve

CRANKSHAFT

DIESEL
 **LOMBARDINI**
 A KOHLER COMPANY


Equipped with:

- Three ceramic pistons, brass linear pump head with built-in by-pass valve.
- 1560 RPM reducer between engine and pump.
- By-pass with safety valve.
- Automatic RPM regulation.
- Electrical start with engine functions control.
- Lombardini diesel engine 15LD400 (air cooled).
- Integrated detergent suction with external suction probe. Pressure regulator.
- Glycerine pressure gauge.
- Suction hose with check valve (**optional**).
- Heavy duty steel frame.
- Battery included.
- 30 lt. Diesel tank.

STANDARD EQUIPMENT

- 3.700.0030 Gun M22 - 3/8" with rotating coupling.



- 3.701.0027 Lance M22 high/low pressure.



- 3.103.0053 Nozzle type 060



- 4.618.0143 High pressure hose 10 m



Optional:

- 5.012.0319 Suction hose with check valve



	Thermic 10 D
code	8.601.0111
operat. pressure	180 bar-2465 psi
delivery rate	1020 l/h-4.49 GPM
engine type/hp	Lombardini 15LD400/10
pump type/RPM	CL5/1560 RPM
max. water inlet temp.	40 °C
dimension/weight	100x66x92cm / 82 Kg - 180 lbs