

Thermic 18 BS/22 H

POWERED by
HONDATM
Only Thermic 22 H



MORE INFO



18BS

MORE INFO



22H

CHARACTERISTICS

- TW Premium/TW 500 bar Premium pumps with brass pump head and ceramic pistons
- Briggs & Stratton Vanguard (Thermic 18 BS)/Honda engine GX 690 (Thermic 22 H)
- Gearbox (with 1560 rpm pump)
- Electrical starting
- Ø 300 industrial wheels with brake
- No engine-oil safety device (oil-alert)
- **Hour counter**
- Automatic decelerator to reduce the number of revs in the bypass phase
- Stainless steel gradual pressure restoration valve with EASY-START
- Thermostatic valve
- Water filter, readily serviceable cartridge type
- Water suction from external tank option (self priming pumps only TW)
- Hose reel with 20 mt hose can be mounted on request (cod. 00080-01521)

TECHNICAL DATA

	Thermic 18 3518 BS	Thermic 22 3521 H	Thermic 22 4018 H	Thermic 22 5015 H	Thermic 22 2730 H
code	36018-00043	36018-00042	36018-00041	36018-00040	36018-00045
rated/max pressure	350/360 bar - 5076/5221 psi	350/360 bar - 5076/5221 psi	400/415 bar - 5801/6019 psi	500/520 bar - 7252/7541 psi	270/280 bar - 3916/4061 psi
max delivery flow rate	1080 l/h - 4.76 gpm	1320 l/h - 5.8 gpm	1110 l/h - 4.8 gpm	990 l/h - 4.3 gpm	1800 l/h - 7.92 gpm
engine type	B&S Vanguard	Honda GX 690/22	Honda GX 690/22	Honda GX 690/22	Honda GX 690/22
motor power	18 hp	22 hp	22 hp	22 hp	22 hp
pump model	TW/1560 rpm	TW/1560 rpm	TW 500/1560 rpm	TW 500/1560 rpm	TW/1560 rpm
T max water inlet	60°C	60°C	60°C	60°C	60°C
dimension (cm)/weight	118,5x74x102/150 Kg (330 lbs)	118,5x74x102/180 Kg (397 lbs)	118,5x74x102/180 Kg (397 lbs)	118,5x74x102/180 Kg (397 lbs)	118,5x74x102/180 Kg (397 lbs)

PLUS



Sturdy painted steel frame with vertical lifting bar, practical side hooks for accessories and protective stainless steel covers to preserve the motor pump from accidental impacts



Vanguard 18hp / Honda 22hp two-cylinder petrol engines with electric starter, automatic decelerator and 20-litre fuel tank











TW Premium / TW 500 pump with brass head and ceramic pistons



Foamed pneumatic wheels in solid rubber and 300 mm diameter steel rims for positioning stability and for movement operations

STANDARD EQUIPMENT

 <ul style="list-style-type: none"> • 00080-01098 Gun ML 955 - M24 with quick coupling (mod. Thermic 18 BS) 	 <ul style="list-style-type: none"> • 00080-01100 Gun ML 710 with quick coupling M24-M24 (mod. Thermic 22H) 	 <ul style="list-style-type: none"> • 10002-04020 lance SF40 M24 (Thermic 18 BS) 	 <ul style="list-style-type: none"> • 10002-04022 Stainless steel Lance 500 bar L70 (mod. Thermic 22H) 	 <ul style="list-style-type: none"> • 00080-01368 Nozzle 040 (mod. 3518 BS) • 00080-00319 Nozzle 050 (mod. 3521 H) • 00080-00317 Nozzle 040 (mod. 4018 H)
 <ul style="list-style-type: none"> • 00080-00355 Nozzle 028 (mod. 5015 H) • 00080-03341 Nozzle 075 (mod. 2730 H) 	 <ul style="list-style-type: none"> • 10002-04110 High pressure hose 10 m (Thermic 18 BS) • 10002-04111 High pressure hose 10 m (Thermic 22H) 	 <ul style="list-style-type: none"> • 00009-02403 Rotating coupling 		

OPTIONAL

<ul style="list-style-type: none"> • Turbo lance code: 10002-04104 (mod.3518) 10002-04097 (mod.3521) 10002-04096 (mod.4018) 10002-04094 (mod.5015) • mod. 2730 on request 	<ul style="list-style-type: none"> • Pipe cleaning hose 25 m. code: 00058-00650 (mod.3518) 00058-00649 (mod.3521/4018) 00058-00648 (mod.5015) • mod. 2730 on request 	<ul style="list-style-type: none"> • Extension hose code: 10002-04106 (mod.3518) 10 m. 10002-04099 (mod.3521/2730) 20 m. 10002-04098 (mod.4018/5015) 20 m. 	<ul style="list-style-type: none"> • Sand-blasting lance 500 bar code: 10002-04108 (mod.3518) 10002-04102 (mod.3521) 10002-04101 (mod.4018) 10002-04100 (mod.5015) • mod. 2730 on request 	<ul style="list-style-type: none"> • 00069-00223 Apron
--	---	---	--	---