

Thermic 26 7013 K













CHARACTERISTICS

- 4 twin solid wheels 350mm diameter Kohler KDW1003 Diesel liquid cooled engine (26hp) TW 700 triplex pumps Gearbox (with 1450 rpm)
- Electrical starting Hours meter RPM manual regulator Stainless steel gradual pressure relief valve with EASY START Stainless steel pressure gauge Safety valve Thermostatic valve Big water filter at pump inlet, readily serviceable cartridge type Suitable for high professional use

TECHNICAL DATA

	Thermic 26 7013 K
code	36018-00063
rated/max pressure	700/770 bar - 10152/11167 psi
max delivery flow rate	780 l/h - 3.43 gpm
engine type	Kohler KDW1003 Diesel
motor power	26 hp
pump model	TW 700/1450 rpm
T max water inlet	60°C
dimension (cm)/weight	137x85x102/300 Kg (661 lbs)

COLD WATER WITH COMBUSTION ENGINE

PLUS



Standard 1000 bar accessories, oversized to ensure the highest level of safety for the operator



Sturdy painted steel frame with vertical lifting bar, practical side hooks for accessories and protective stainless steel covers to preserve the motor pump from accidental impacts



Kohler KDW 1003 water-cooled engine, 3 cylinders in line to minimise vibrations



TW Premium 700 pump with nickelplated brass head and ceramic pistons

STANDARD EQUIPMENT



• 00080-04552 Nozzle type 025 | • 00042-00243 Safety sock for gun 700 bar







OPTIONAL

• 00080-04622 Turbo nozzle

• 00080-01226 Sand blasting lance

