

Thermic 2W PRO



CRANKSHAFT



GASOLINE

POWERED by
HONDA™

NEW



Equipped with:

- 1560 RPM reducer between engine and pump.
- Self-priming CL5 Lavor pump, 3 ceramic pistons, brass pump head and unloader valve flanged • Suction and delivery S. S. valves.
- Unleaded gasoline engine 13 HP **Honda** GX 390 (Thermic 2W PRO 13 H)
- Unleaded gasoline engine 13 HP **Loncin** G 390F (Thermic 2W PRO 13 L)
- 5 litres detergent tank with filter and cap • Readily serviceable suction water filter
- Oil-alert safety device for engine protection • Glycerine pressure gauge.
- Folding handle with aluminium hinges • Ø 300 big pneumatic wheels; easy to handle also up and down steps and over uneven ground
- S/S pump cover on request

	Thermic 2W PRO 13 L	Thermic 2W PRO 13 H
code	0.066.0037	0.066.0036
operat. pressure/max	250/260 bar-3625/3770 psi	250/260 bar-3625/3770 psi
delivery rate	1080 l/h-4.76 GPM	1080 l/h-4.76 GPM
engine type/hp	Loncin G 390F/13	Honda GX 390/13
pump type/RPM	CL5/1560 RPM	CL5/1560 RPM
max. water inlet temp.	60 °C	60 °C
dimension/weight	85x58x105cm / 65 Kg - 143 lbs	85x58x105cm / 65 Kg - 143 lbs

STANDARD EQUIPMENT

- 0.966.0083 Gun M22 - 3/8 with rotating coupling.



- 0.966.0084 Lance M22 high/low pressure



- 3.103.0196 Inox 350 bar nozzle type 037



- 0.966.0086 High pressure hose 10 m



Optional:

- Hose reel kit cod. 0.966.0107 hose included (15 m)
- 0.966.0082 ROTOX lance 255 bar
- 4.618.0012 Extension hose 10 m
- 4.618.0057 Extension hose 20 m
- 5.012.0319 Suction hose with check valve

