

Thermic 2W PRO

POWERED by
HONDATM
Only Thermic 2W PRO 13 H



MORE INFO



CHARACTERISTICS

- Gearbox reducer between engine and pump (1560 rpm) • Self-priming CL6.0 Lavor pump, 3 ceramic pistons, brass pump head and unloader valve flanged • Suction and delivery Stainless steel valves. • Unleaded gasoline engine 13 hp **Honda** GX 390 (Thermic 2W PRO 13 H) • Unleaded gasoline engine 13 hp **Loncin** G 390F (Thermic 2W PRO 13 L) • 5 litres detergent tank with filter and cap • Readily serviceable suction water filter • Oil-alert safety device for engine protection • Glycerine pressure gauge. • Folding handle with aluminium hinges • Ø 300 big pneumatic wheels; easy to handle also up and down steps and over uneven ground • Stainless steel pump cover on request

TECHNICAL DATA

	Thermic 2W PRO 13 L	Thermic 2W PRO 13 H
code	36021-00038	36021-00037
rated/max pressure	250/260 bar - 3625/3770 psi	250/260 bar - 3625/3770 psi
max delivery flow rate	1020 l/h - 4.4 gpm	1020 l/h - 4.4 gpm
engine type	Loncin G 390F	Honda GX 390
motor power	13 hp	13 hp
pump model	CL6.0/1560 rpm	CL6.0/1560 rpm
T max water inlet	60°C	60°C
dimension (cm)/weight	85x58x105/65 Kg (143 lbs)	85x58x105/65 Kg (143 lbs)

PLUS



New CL 6.0 self-priming pump with three pistons in integral ceramic, double oil viewer and brass head. Speed reducer between motor and pump. New flanged pressure regulating valve L3.1, internal passages resized to ensure correct operation even in high operating flow conditions



Ergonomic handle in painted steel adjustable by means of hinged joints, foldable to reduce dimensions and to improve portability







Robust tubular frame in painted steel with anti-vibration front feet for stability, inflatable rear wheels with a diameter of 300 mm to facilitate movement on any type of surface, stainless steel fairing.




Integrated detergent tank with external probe for indirect suction of the chemical product

STANDARD EQUIPMENT

 <ul style="list-style-type: none"> • 00080-01695 Gun M22 - 3/8 with rotating coupling. 	 <ul style="list-style-type: none"> • 00080-01739 Lance M22 high/low pressure 	 <ul style="list-style-type: none"> • 00080-03329 Inox 350 bar nozzle type 037 inox 	 <ul style="list-style-type: none"> • 00014-00514 High pressure hose 10 m 	
---	---	---	--	--

OPTIONAL

 <ul style="list-style-type: none"> • 10002-12275 Suction hose with check valve 	<ul style="list-style-type: none"> • Hose reel kit cod. 00080-01524 hose included (15 m) 	<ul style="list-style-type: none"> • 10002-03408 Turbo lance 255 bar 	<ul style="list-style-type: none"> • 00080-02258 Extension hose 10 m 	<ul style="list-style-type: none"> • 00080-02262 Extension hose 20 m
---	---	---	---	---