

Thermic 5H









CHARACTERISTICS

- Three ceramic coated pistons, brass axial pump head with built-in by-pass valve. Suction and delivery Stainless steel valves. 5 hp **Honda** GP 160 unleaded gasoline engine. Manual start Integrated detergent suction with external suction probe. Pressure regulator.
- Glicerine pressure gauge. Hose reel (optional). Suction hose with check valve (optional). Steel frame. Hose holder. 3,1 l gasoline tank.

TECHNICAL DATA

	Thermic 5H
code	36113-00053
rated/max pressure	160/190 bar - 2320/2755 psi
max delivery flow rate	570 l/h - 2.51 gpm
engine type	Honda GP 160
motor power	5 hp
pump model	TPBH4/3400 rpm
T max water inlet	40°C
dimension (cm)/weight	70x59x97/37 Kg (81 lbs)



PROFESSIONAL LINE HIGH PRESSURE CLEANERS

COLD WATER WITH COMBUSTION ENGINE

PLUS



Linear self-priming pump with three ceramic pistons and brass head



Sturdy painted steel frame with rear wheels and anti-vibration front foot for stable positioning, handle with ergonomic handle for easy movement on any type of surface



Side support for lance and gun housing



Pneumatic wheels to dampen vibrations and to promote movement on any type of surface

STANDARD EQUIPMENT







• 00080-03186 Nozzle type 035



• 00080-02254 High pressure hose 8 m

OPTIONAL

• 10001-10200 High-pressure hose reel (hose not included)



• 10002-12275 Suction hose with check valve

hose - 3/8" M22 - Ø 1/4" - 210 bar

• 00080-02254 8 m High pressure | • 00080-02261 20 m High pressure | • 00080-02957 Sandblasting lance hose - 3/8" - Ø 5/16" - 400 bar