

Thermic 9 L











CHARACTERISTICS

• Three ceramic coated pistons, brass linear pump head with built-in by-pass valve • Suction and delivery stainless steel valves • Manual start • 9 hp unleaded gasoline engine. • By-pass with safety valve. • Integrated detergent suction with external suction probe. • Pressure regulator. • Suction hose with check valve (optional). • Hose holder. • Nozzles holder. • 4 l gasoline tank.

TECHNICAL DATA

	Thermic 9 L
code	36113-00033
rated/max pressure	220/250 bar - 3190/3625 psi
max delivery flow rate	900 l/h - 3.96 gpm
engine type	Loncin
motor power	9 hp
pump model	TPBH5/3400 rpm
T max water inlet	40°C
dimension (cm)/weight	50x67x103/45 Kg (101 lbs)

COLD WATER WITH COMBUSTION ENGINE

PLUS



Linear self-priming pump with three ceramic pistons and brass head



Sturdy painted steel frame with rear wheels and anti-vibration front foot for stable positioning, handle with ergonomic handle for easy movement on any type of surface



Side support for lance and gun housing and nozzle holder base



Pneumatic wheels to dampen vibrations and to promote movement on any type of surface

STANDARD EQUIPMENT



 00080-02770 Lance M22 with nozzle-holder.





OPTIONAL



• 10002-12275 Suction hose with check valve

High pressure hose code:
00080-02258 10 m - 310 bar
00080-02261 20 m - 400 bar
00080-02264 10 m R2

• 00080-02966 Lance Turbo type 1 M22 - 0,45

• 00080-02957 Sandblasting lance