

HKA







CHARACTERISTICS

- Three steel pistons, brass axial pump head with built-in by-pass valve. Pump with double seal Total Stop. Suction and delivery Stainless steel valves.
- Detergent built-in tank for indirect suction. Power cable holder. Hose reel in pressure. Accessory holder. Ergonomic handle. 11 detergent tank.

TECHNICAL DATA

	HKA 1409 XP
code	36087-00006
rated/max pressure	140/180 bar - 2030/2610 psi
max delivery flow rate	540 l/h - 2.4 gpm
abs. power/supply	2800 W/230V 1~50Hz
motor power	2,0 kW
pump model	MPBX1/2800 rpm
T max water inlet	40°C
dimension (cm)/weight	35x40x96/28 Kg (61,6 lbs)

COLD WATER

PLUS



Axial motor pump with stainless steel pistons, brass head, double water seal



Practical hose reel connected under pressure to use only the necessary length of hose and to rewind it easily after use



Convenient and functional rotary switch for easy switching on and off



Integrated cleaning tank with a capacity of 1 litre for indirect suction of the chemical with a level visible from the outside

STANDARD EQUIPMENT







• 00080-03186 Nozzle type 035



• 00080-02294 High pressure hose R1 8 m

OPTIONAL