

Indo E



Equipped with:

- Motor 12-15 hp
- Heavy duty structure with stainless steel covers
- High filtering capacity cartridge suction brass filter
- TW Triplex Premium pumps
- Pressure gauge with stainless steel casing
- **Hot water seals 4-poles (1450 rpm)** motor well oversized and protected with paint. Ø 300 wheels with brake
- Highly professional unloader valve with external bypass
- **Motor-pump with flexible joint**
- Timed Total Stop
- Low voltage control panel
- Contactor
- Thermal relay motor protection
- Hose reel with 20 mt hose can be mounted on request (cod. 0.966.0033 mod. 2521/cod. 0.966.0034 mod. 3518)
- Practical and safe housing accessories

On request 60Hz version

	Indo 2521 E LP	Indo 3518 E LP	Indo 2030 E LP
code	0.066.0006	0.066.0007	0.066.0053
operat. pressure	250 bar-3626 psi	350 bar-5076 psi	200 bar-2900 psi
delivery rate	1260 l/h-5.55 GPM	1080 l/h-4.75 GPM	1800 l/h-7.9 GPM
abs. power/voltage	10000W - 400 V~50 Hz 3 ph	12000W - 400 V~50 Hz 3 ph	12000W - 400 V~50 Hz 3 ph
motorpump type/RPM	TW/1450 RPM	TW/1450 RPM	TW/1450 RPM
max. water inlet temperature	85 °C	85 °C	85 °C
dimension/weight	126x74x98cm/125 Kg - 275,5 lbs	126x74x98cm/130 Kg - 286,5 lbs	126x74x98cm/130 Kg - 286,5 lbs

STANDARD EQUIPMENT

- 0.966.0003 Gun ML 955 - M22 with quick coupling (mod. 2521/2030)
- 0.966.0004 Gun ML 955 - M24 with quick coupling (mod. 3518)



- 0.966.0007 lance SF40 mecline M22 (mod.2521/2030)
- 0.966.0008 lance SF40 mecline M24 (mod.3518)



- 0.966.0037 Nozzle type 040 (mod. 3518 LP)
- 0.966.0036 Nozzle type 055 (mod. 2521 LP)
- 3.103.0206 Nozzle type 2510 (mod. 2030 LP)



- 0.966.0011 High pressure hose 10 m (mod.2521/2030)
- 0.966.0012 High pressure hose 10 m (mod.3518)



- Power cable 5 m

Optional:

Rotox lance

- 0.966.0014 (mod. 2521)
 - 0.966.0015 (mod. 3518)
- for model 2030: on request

Pipe cleaning hose 25 m.

- 0.966.0020 (mod. 2521)
 - 0.966.0021 (mod.3518)
- for model 2030: on request

Extension hose 10 m.

- 0.966.0024 (mod. 2521)
- 0.966.0025 (mod. 3518)

- Sand-blasting lance 500 bar
 - 0.966.0028 (mod. 2521/2030)
 - 0.966.0029 (mod. 3518)
- for model 2030: on request