

KAB 1408



NEW



KAB 1408 LP model



KAB 2W 1408 LP model

CHARACTERISTICS

- Three pistons, aluminium pump head with built-in by-pass valve • Total stop • Suction and delivery Stainless steel valves. • Integrated detergent suction with external suction probe • Pressure regulator. • Glycerine pressure gauge. • Accessory holder. • Ergonomic handle.
- Trolley with wheels Ø 250 mm (only model 2W)

TECHNICAL DATA

	KAB 1408 LP	KAB 2W 1408 LP
code	36153-00004	on request
rated/max pressure	130/140 bar - 1885/2030 psi	130/140 bar - 1885/2030 psi
max delivery flow rate	565 l/h - 2.4 gpm	565 l/h - 2.4 gpm
abs. power/supply	2400 W/230V 1~50Hz	2400 W/230V 1~50Hz
motor power	2,1 kW	2,1 kW
pump model	CL2.5/2800 rpm	CL2.5/2800 rpm
T max water inlet	40°C	40°C
dimension (cm)/weight	47x43x37/21 Kg (46 lbs)	58x49,5x56/28 Kg (61,6 lbs)

PLUS



Linear motor pump with stainless steel valves and aluminium head



Convenient and functional rotary switch for easy switching on and off



Ergonomic handle with anti-vibration feet for stability (Kab). Trolley version (2W) with large rear wheels with a diameter of 250 mm to improve its transportation capacity



Sturdy painted steel frame handle for easy movement

STANDARD EQUIPMENT

 <ul style="list-style-type: none"> • 00080-02541 Gun G1/4" M 	 <ul style="list-style-type: none"> • 00080-05320 Lance M22 high/low pressure 	 <ul style="list-style-type: none"> • 00080-02420 High pressure hose 8 m 		
---	---	--	--	--

OPTIONAL

--	--	--	--	--