

KAB 1509



NEW



KAB 1509 LP model



KAB 2W 1509 LP model

CHARACTERISTICS

- Three ceramic coated pistons, overdimensioned brass linear pump head with built-in by-pass valve.
- Total stop
- Suction and delivery Stainless steel valves.
- Integrated detergent suction with external suction probe
- Pressure regulator.
- Glycerine pressure gauge.
- Accessory holder.
- Ergonomic handle.
- Trolley with wheels Ø 250 mm (only model 2W)

TECHNICAL DATA

	KAB 1509 LP	KAB 2W 1509 LP
code	36153-00001	on request
rated/max pressure	130/140 bar - 1885/2030 psi	130/140 bar - 1885/2030 psi
max delivery flow rate	565 l/h - 2.4 gpm	565 l/h - 2.4 gpm
abs. power/supply	2400 W/230V 1~50Hz	2400 W/230V 1~50Hz
motor power	2,1 kW	2,1 kW
pump model	CL4.0/2800 rpm	CL4.0/2800 rpm
T max water inlet	40°C	40°C
dimension (cm)/weight	47x43x37/23 Kg (50 lbs)	58x49,5x56/30 Kg (66 lbs)

PLUS



Linear motor pump with stainless steel valves and brass head



Convenient and functional rotary switch for easy switching on and off



Ergonomic handle with anti-vibration feet for stability (Kab). Trolley version (2W) with large rear wheels with a diameter of 250 mm to improve its transportation capacity



Sturdy painted steel frame handle for easy movement

STANDARD EQUIPMENT

 <ul style="list-style-type: none"> • 00080-02541 Gun G1/4" M 	 <ul style="list-style-type: none"> • 00080-05320 Lance M22 high/low pressure 	 <ul style="list-style-type: none"> • 00080-02420 High pressure hose 8 m 		
---	---	--	--	--

OPTIONAL

--	--	--	--	--