

Lite PRO/Lite PRO 2W









MORE INFO



LITE PRO

MORE INFO



LITE PRO 2W

CHARACTERISTICS

• Three full ceramic pistons, brass linear pump head with by-pass valve • Easy to transport thanks to a practical top grip and anti-vibration supports (only model Lite) • Trolley with wheels Ø 250 mm (only 2W model) • 4-pole motor (1400 rpm) • Glicerine pressure gauge. • EASY START device • Total Stop system • Rotary switch • Motor thermal protection

TECHNICAL DATA

	LITE PRO 1510 XP	LITE PRO 2W 1510 XP
code	36016-00020	36016-00024
rated/max pressure	140/150 bar - 2030/2175 psi	140/150 bar - 2030/2175 psi
max delivery flow rate	600 l/h - 2.64 gpm	600 l/h - 2.64 gpm
abs. power/supply	2900 W/230V 1~50Hz	2900 W/230V 1~50Hz
motor power	2,1 kW	2,1 kW
pump model	CL3.1/1400 rpm	CL3.1/1400 rpm
T max water inlet	60 °C	60 °C
dimension (cm)/weight	26x47x37/35 Kg (77 lbs)	60x43x93/40 Kg (88 lbs)

PLUS



4 pole induction motor (1400 rpm): the low rotation speed significantly extends the life of the components inside the motor pump, guaranteeing greater efficiency and silence



Integral ceramic self-priming threepiston linear pump, the best solution for a professional product



Sturdy painted steel frame with anti-vibration feet for stability, ergonomic handle for easy movement (Lite). Trolley version (2W) with large rear wheels with a diameter of 250 mm to improve its transportation capacity



Hose reel (optional on the Trolley version) connected under pressure to use only the necessary length of hose and to rewind it easily after

STANDARD EQUIPMENT



• 10002-03553 Lance M22 high/low pressure



• 00080-01368 Stainless steel nozzle type 040



• 00014-00276 High pressure hose 10 m

• 00070-00052 Detergent filter

OPTIONAL