

# Lite/Lite 2W



## **CHARACTERISTICS**

• Three steel pistons, brass axial pump head with built-in by-pass valve • Easy to transport thanks to a practical top grip and anti-vibration supports (only model Lite) • Induction 2-pole motor (2800 rpm) • Trolley with wheels Ø 250 mm (only 2W model) • Glicerine pressure gauge. • EASY START device • Total Stop system • Rotary switch • Motor thermal protection

## **TECHNICAL DATA**

	LITE 1510 XP	LITE 2W 1510 XP
code	36016-00019	36016-00023
rated/max pressure	135/150 bar - 1958/2175 psi	135/150 bar - 1958/2175 psi
max delivery flow rate	600 l/h - 2.64 gpm	600 l/h - 2.64 gpm
abs. power/supply	2900 W/230V 1~50Hz	2900 W/230V 1~50Hz
motor power	2,1 kW	2,1 kW
pump model	GXR/2800 rpm	GXR/2800 rpm
T max water inlet	60°C	60°C
dimension (cm)/weight	26x47x37/25 Kg (55 lbs)	60x43x93/30 Kg (66 lbs)

#### **PLUS**



Axial motor pump with stainless steel pistons, brass head, double water seal



Convenient and functional rotary switch for easy switching on and off



Sturdy painted steel frame with anti-vibration feet for stability, ergonomic handle for easy movement (Lite). Trolley version (2W) with large rear wheels with a diameter of 250 mm to improve its transportation capacity



Hose reel (optional on the Trolley version) connected under pressure to use only the necessary length of hose and to rewind it easily after

# **STANDARD EQUIPMENT**



# OPTIONAL

• 10002-03655 Turbo lance	• 10002-04322 2 Wheels cart	• 00080-01541 Hose-reel kit (only 2W model)	• 00058-00632 25 m pipe cleaning hose	
---------------------------	-----------------------------	--	---------------------------------------	--