

## Lite PRO/Lite 2W PRO

**T.S.** Total Stop



CRANKSHAFT

1450 RPM



LITE 2W PRO 1510 LP model



LITE PRO 1510 LP model

**NEW**

### Equipped with:

- Three full ceramic pistons, brass linear pump head with by-pass valve
- Easy to transport thanks to a practical top grip and anti-vibration supports
- Trolley with wheels Ø 250 mm (only 2W model)
- 4-pole motor (1450 rpm)
- Glycerine pressure gauge.
- EASY START device
- Total Stop system
- Rotary switch
- Motor thermal protection

### STANDARD EQUIPMENT

- 3.700.0036 Gun G3/8" M



- 0.966.0094 Lance M22 high/low pressure



- 0.966.0037 S.S. nozzle



- 0.966.0099 H.p. hose 10 m



- Power cable 5 m

### Optional:

- 3.712.0010 ROTOX lance
- 3.555.1134 2W cart
- 3.555.1135 Hose-reel kit (only 2W model)

	LITE PRO 1510 LP	LITE 2W PRO 1510 LP
code	0.066.0032	0.066.0052
operat. pressure/max	135/150 bar-1958/2175 psi	135/150 bar-1958/2175 psi
delivery rate	600 l/h-2.64 GPM	600 l/h-2.64 GPM
abs. power/voltage	2900W - 230V~50Hz 1 ph	2900W - 230V~50Hz 1 ph
motor/pump type/RPM	CL3.1/1400 RPM	CL3.1/1400 RPM
max. water inlet temperature	60 °C	60 °C
dimension/weight	26x47x37cm/35 Kg - 77 lbs	60x43x93 cm/40 Kg - 88 lbs