

**Lite/Lite 2W**

**T.S.** Total Stop

**STANDARD EQUIPMENT**

- 6.001.0143 Gun G1/4" M



- 0.966.0096 Lance M22 high/low pressure



- 0.966.0097 Nozzle



- 0.966.0098 H.p. hose 10 m



- Power cable 5 m

Optional:

- 0.966.0100 ROTOX lance
- 3.555.1134 2 Wheels cart
- 3.555.1135 Hose-reel kit (only 2W model)



LITE 1510 XP model

**NEW**



LITE 2W 1510 XP model

**Equipped with:**

- Three steel pistons, brass axial pump head with built-in by-pass valve
- Easy to transport thanks to a practical top grip and anti-vibration supports
- Induction 2-pole motor (2800 rpm)
- Trolley with wheels Ø 250 mm (only 2W model)
- Glycerine pressure gauge.
- EASY START device
- Total Stop system
- Rotary switch
- Motor thermal protection

	LITE 1510 XP	LITE 2W 1510 XP
code	0.066.0031	0.066.0051
operat. pressure/max	135/150 bar-1958/2175 psi	135/150 bar-1958/2175 psi
delivery rate	600 l/h-2.64 GPM	600 l/h-2.64 GPM
abs. power/voltage	2900W - 230V~50Hz 1 ph	2900W - 230V~50Hz 1 ph
motor/pump type/RPM	GXR/2800 RPM	GXR/2800 RPM
max. water inlet temperature	60 °C	60 °C
dimension/weight	26x47h37cm/25 Kg - 55 lbs	60x43h93 cm/30 Kg - 66 lbs