

Maine



MORE INFO




CHARACTERISTICS

- Three steel pistons, brass axial pump head with built-in by-pass valve.
- Double water seal
- Total Stop.
- Suction and delivery Stainless steel valves.
- Integrated detergent suction with external suction probe.
- Power cable holder.
- High pressure hose holder.
- Accessory holder.
- Ergonomic handle.

TECHNICAL DATA

	Maine 1409 XP
code	36091-00001
rated/max pressure	140/180 bar - 2030/2610 psi
max delivery flow rate	540 l/h - 2.4 gpm
abs. power/supply	2800 W/230V 1~50Hz
motor power	2,0 kW
pump model	MPBX1/2800 rpm
T max water inlet	40°C
dimension (cm)/weight	39x39x71/23 Kg (50,7 lbs)

PLUS



Axial motor pump with stainless steel pistons, brass head, double water seal



Ergonomic handle for lifting and manual transportation, it can also serve as a practical reel for electrical cable or high-pressure pipe



Convenient and functional rotary switch for easy switching on and off



Folding handle to reduce dimensions and to facilitate movement. If fully extended it makes it possible to pull the product on the rear wheels

STANDARD EQUIPMENT

 <ul style="list-style-type: none"> • 00080-02541 Gun M22 	 <ul style="list-style-type: none"> • 00080-02804 Lance M22 high/low pressure 	 <ul style="list-style-type: none"> • 00080-02420 High pressure hose 8 m 		
---	---	--	--	--

OPTIONAL

<ul style="list-style-type: none"> • 00080-02957 Sandblasting lance 	<ul style="list-style-type: none"> • 00080-02981 Turbo lance 			
--	---	--	--	--