

Mystic-R







CHARACTERISTICS

- Three steel pistons, brass axial pump head with built-in by-pass valve. Pump with double seal Total stop. Suction and delivery Stainless steel valves. Detergent built-in tank for indirect suction. Glicerine pressure gauge. Hose holder. Accessory holder. Ergonomic handle.
- Power cable 5 m

TECHNICAL DATA

	Mystic-R 1409 XP
code	36084-00005
rated/max pressure	140/180 bar - 2030/2610 psi
max delivery flow rate	540 l/h - 2.4 gpm
abs. power/supply	2800 W/230V 1~50Hz
motor power	2,0 kW
pump model	MPBX1/2800 rpm
T max water inlet	40°C
dimension (cm)/weight	43x50x85/28 Kg (61,6 lbs)

COLD WATER

PLUS



Axial motor pump with stainless steel pistons, brass head, double water seal



Glycerine bath pressure gauge to constantly monitor the operating pressure of the high pressure cleaner with reading guarantee



Integrated cleaning tank for indirect suction of the chemical product



Sturdy protective steel cover to protect the motor pump against accidental impacts

STANDARD EQUIPMENT



• 00080-02576 Gun M22



• 00080-02770 Lance M22.





OPTIONAL

• 10001-10252 High-pressure wall mount hose reel (hose not included)

• 00080-03481 Turbo nozzle head • 00080-02981 Turbo lance M22 - 0,35 • 00080-02957 Sand blasting lance M22 - 0,40