

Arizona

T.S. Total Stop



STANDARD EQUIPMENT

- 6.001.0143 Gun M22



- 6.002.0322 Lance M22.



- 5.012.0478 High pressure nozzle set (mod. 1209 LP)
- 5.012.0401 High pressure nozzle set (mod. 1311 LP)



- 4.618.0128 High pressure hose 8 m



- Power cable 5 m

Available versions:

Code: **8.665.0110**

Arizona 1311 LP **with hose reel** (10 m high pressure hose code 4.618.0053)

Code: 3.749.0472 Rotox head (mod. 1209 LP)

Equipped with:

- 4 poles electrical motor (1450 RPM) with thermal protection.
- Three ceramic coated pistons, brass linear pump head with built-in by-pass valve.
- Suction and delivery S. S. valves.
- Detergent built-in tank for indirect suction.
- Pressure regulator.
- Glycerine pressure gauge.
- Hose reel (**optional**).
- Accessory holder.
- Hose-holder.
- Ergonomic handle.
- 7,5 lt. detergent tank.

| | Arizona 1209 LP | Arizona 1311 LP |
|------------------------------|---------------------------|---------------------------|
| code | 8.665.0101 | 8.665.0106 |
| operat. pressure/max | 120/150 bar-1740/2175 psi | 130/150 bar-1885/2175 psi |
| delivery rate | 510 l/h-2.23 GPM | 660 l/h-2.90 GPM |
| abs. power/voltage | 2300W - 230V~50Hz 1 ph | 2900W - 230V~50Hz 1 ph |
| motor/pump type/RPM | MP3/1450 RPM | MP3/1450 RPM |
| max. water inlet temperature | 40 °C | 40 °C |
| dimension/weight | 59x37x87cm/26 Kg - 57 lbs | 59x37x87cm/28 Kg - 61 lbs |