

Comfort M

LEVEL



STOP



Equipped with:

- Suitable for maintenance and deep cleaning of medium and large areas (up to 6.000 m²)
- More than 90/120 kg of constant pressure on the brushes
- Large load tank capacity, resulting in reduced number of stops and maximum use of battery charge for effective operation of the machine
- Stability even when fully loaded
- Front independent wheel-drive with tight steering radius
- Easy access to electrical components
- Automatic brush plate lifting system
- Automatic squeegee lifting system
- Automatic squeegee lifting while reverse going
- Automatic control system for brush rotation and detergent water outflow
- Antifoam device
- Self-levelling brush plate
- Hour meter
- High-performance batteries resulting in high-working efficiency.
- Quick refilling system

*** New, standard on machines starting from 2022, compatible with all previous machine models**

STANDARD EQUIPMENT



- 2 x 5.511.2248
PP brush Ø 483 mm - 19"



- 4.508.0217
Front squeegee blade L.1270 mm
Shore 40 Th. 4 mm
- 4.508.0216
Rear squeegee blade L.1345 mm
Shore 33 Th. 6 mm

	Comfort M 102
code	8.578.0004
power supply	36V
scrubbing/squeegee width	1020/1250 mm
max working capacity	7140 m ² /h
solution tank capacity	200 l/52.84 gal
recovery tank capacity	210-240 l/55.5-63.4 gal
traction type/power	front motorwheel/900 W
RPM/pressure on the brushes	150/120 kg/246 lbs
brush motor power	1500 W
max gradient empty/full tank	10%/8%
depression/vacuum motor	1800 mmH ₂ O/550 W
dimensions/weight	190x112x145 cm/342 kg

OPTIONAL



The unique anti foam device dramatically reduces the foam generation and prevents it from touching the suction motor, thus protecting its operation. The electronic floating switch stops suction when the tank is full. Large tank opening for fast and easy cleaning and sanification.

The strong V-shaped floor squeegee made of steel profile is widely adjustable and allows to combine the operation of the rubber blades with the high suction power, to get a perfect drying result on every surface. The special filter box retains solid debris and prevents the obstruction of the suction hose.



- 0.107.0009
Battery box Pb-acid
36V 360Ah C5
- 0.107.0012
Gel battery box
36V 320Ah C5

- 0.108.0003
Battery Charger 24V/36V
50/60A - 220-240/50-60

- 4.508.1167 Polyurethane front blade L.1270 TH. 4
- 4.508.0897 Polyurethane rear blade L.1345 TH. 6

- * • 2x 5.511.2239
Tynex brush Ø 483 mm-19"
- 2x 5.511.2240
PP 0,3 brush Ø 483 mm-19"
- 2x 5.511.2241
PES brush Ø 483 mm - 19"

- * • 2x 5.511.2242
EWU pad driver Ø 483 mm-19"



Comfort M scrubbers are easy to use thanks to the simple and user friendly controls. From the control panel the operator can adjust the maximum forward speed and the quantity of cleaning solution outflow, selecting the options most suitable to the dirt type. Job is simplified and made faster by the automatic lifting of the squeegee and of the brush plate.

- 6.508.0034 - Ø 483 mm - 19"- beige (5 pcs.)
- 6.508.0041 - Ø 483 mm - 19"- green (5 pcs.)
- 6.508.0048 - Ø 483 mm - 19"- black (5 pcs.)

Thanks to the optimal weight distribution and to the use of strong oil-proof polyurethane wheels the drive is perfect in all working conditions. The emptying of the solution water tank is quick with a simple and easy accessible mechanical tap.

