

## Comfort S-R 90

### LEVEL



STOP



\*



• 2 x 5.511.2233  
PP brush Ø 457 mm - 18"



• 4.508.1196  
Front squeegee blade L.1027 mm  
Shore 40 Th. 3 mm  
• 4.508.1195  
Rear squeegee blade L.1150 mm  
Shore 33 Th. 4 mm

### Equipped with:

- Suitable for maintenance and deep cleaning of medium and large areas (up to 4.500 m<sup>2</sup>) with a considerable reduction of cleaning costs
- More than 50 kg of constant pressure on the brushes
- Large load tank capacity, resulting in reduced number of stops and maximum use of battery charge for effective operation of the machine
- Stability even when fully loaded
- Front independent wheel-drive with tight steering radius
- Easy access to electrical components
- Automatic brush plate lifting system
- Automatic squeegee lifting system
- Automatic squeegee lifting while reverse going
- Automatic device that stops brushes and detergent water outflow when the machine is stationary
- Antifoam device
- Self-levelling brushes
- High-performance batteries resulting in high-working efficiency.

**\* New, standard on machines starting from 2022, compatible with all previous machine models**

	Comfort S-R 90
code	8.575.0010
power supply	24V
scrubbing/squeegee width	900/1000 mm
max working capacity	6200 m <sup>2</sup> /h
solution tank capacity	140 l/36.99 gal
recovery tank capacity	150-180 l/39.6-47 gal
traction type/power	front motorwheel/1000 W
RPM/pressure on the brushes	150/50 kg/176 lbs
brush motor power	1250 W
max gradient empty/full tank	10%/7%
depression/vacuum motor	1734 mmH <sub>2</sub> O/550W
dimensions/weight	180x103x150 cm/264 kg

**OPTIONAL**



Quick lock recovery tank cap allows for fast and easy cleaning and sanitization of the tank; the tilting tank together with a large size drain hose allow the complete emptying of the tank and the removal of any type of solid dirt. The antifoam device protects suction motor, as well as the electronic floating switch that stops suction when the tank is full.



• 0.107.0008  
Battery box Pb-acid  
24V 500Ah C5

• 0.107.0011  
Gel battery box  
24V 400Ah C5



• 0.108.0003  
Battery Charger 24V/36V  
50/60A - 220-240/50-60



• 4.508.1251 Polyurethane  
front blade L.1027 TH. 3  
• 4.508.1252 Polyurethane  
rear blade L.1150 TH. 4

Comfortable steering wheel.  
User friendly control panel,  
provided with hour meter, speed  
adjustment knob and detergent  
solution low level warning light.  
All motors are protected by  
thermal breakers.




\*



• 2x 5.511.2234  
Tynex brush Ø 457 mm-18"  
• 2x 5.511.2235  
PP 0,3 brush Ø 457 mm-18"  
• 2x 5.511.2236  
PES brush Ø 457 mm-18"

\*



• 2x 5.511.2237  
EWU pad driver Ø 457 mm-18"



50 kg of continuous brush plate  
pressure with Self Leveling  
System to strongly and deeply  
removing any kind of dirt on  
any kind of floor.  
Strong oil-proof polyurethane  
wheels.

500 Ah C5 battery box  
allowing continuous working  
time up to 5 hours.



• 6.508.0150 - Ø 457 mm-18"-  
beige (5 pcs.)  
• 6.508.0151 - Ø 457 mm-18"-  
green (5 pcs.)  
• 6.508.0142 - Ø 457 mm-18"-  
black (5 pcs.)

Built with strong components,  
Comfort S-R have been designed  
to resist even to extreme stresses;  
the frame is made of steel profiles  
with a thickness varying from 5  
to 12 mm, protected with a high  
resistance corrosion-proof paint.

