

Comfort XS-R1 Up

LEVEL



CHARGER



STOP



NEW



Equipped with:

- Capable to work for the maintenance and deep cleaning of large areas (up to 4.000 m²) with a considerable reduction of cleaning costs
- More than 50 kg of constant pressure on the brushes
- Large load tank capacity, resulting in reduced number of stops and maximum use of battery charge for effective operation of the machine
- Compact size (810 mm)
- Stability even when fully loaded, front independent wheeldrive with tight steering radius
- Recovery tank control window for cleaning and easy ordinary maintenance
- Automatic brush plate lifting system
- Automatic squeegee lifting system
- Automatic squeegee lifting while reverse going
- Automatic device that stops brushes and detergent water outflow when the machine is stationary
- Antifoam device
- Self-levelling brushes
- Integrated on-board battery charger (only for model code: 8.574.5101 - 8.574.5103).
- Automatic brush release
- Separate eco mode for brush and suction

*** New, standard on machines starting from 2022, compatible with all previous machine models**

STANDARD EQUIPMENT

- * **Comfort XS-R1 75 Up**
- 2 x 5.511.2218
 - PP brush Ø 360 mm - 14"

- * **Comfort XS-R1 85 Up**
- 2 x 5.511.2255
 - PP brush Ø 430 mm - 17"

- Comfort XS-R1 75 Up**
- 4.508.0646
 - Front squeegee blade L.925 mm
 - Shore 40 Th. 3 mm
 - 4.508.0605
 - Rear squeegee blade L.1015 mm
 - Shore 30 Th. 4 mm

- Comfort XS-R1 85 Up**
- 4.508.1196
 - Front squeegee blade L.1027 mm
 - Shore 40 Th. 3 mm
 - 4.508.1195
 - Rear squeegee blade L.1150 mm
 - Shore 33 Th. 4 mm



- 0.108.0054
- On-board Battery charger
- 24V 20A
- (only for model code: 8.574.5101 - 8.574.5103)

	Comfort XS-R1 75 Up	Comfort XS-R1 85 Up
code	8.574.5101	8.574.5103
power supply	24V (battery charger included)	24V (battery charger included)
scrubbing/squeegee width	750/900 mm	850/1000 mm
max working capacity	4350 m ² /h	5000 m ² /h
solution tank capacity	110 l/29.05 gal	110 l/29.05 gal
recovery tank capacity	130-155 l/34.35-40.95 gal	130-155 l/34.35-40.95 gal
traction type/power	front motorwheel/600 W	front motorwheel/600 W
RPM/pressure on the brushes	170/50 kg/110.23 lbs	170/50 kg/110.23 lbs
brush motor power	2 x 400 W	2 x 400 W
max gradient empty/full tank	13%/10%	13%/10%
depression/vacuum motor	1300 mmH ₂ O/400W	1300 mmH ₂ O/400W
dimensions/weight	146x81x138 cm/189 kg	146x87x138 cm/195 kg



The easy access to the recovery tank allows fast cleaning and sanitification of the tank; the tilting tank together with a large size drain hose allow the complete emptying of the tank and the removal of any type of solid dirt. The antifoam device protects suction motor, as well as the electronic floating switch that stops suction when the tank is full.

Comfort XS-R1 Up is equipped with actuators for the automatic lifting of the brush plate and squeegee. New control panel with digital controls and display. Digital display: with hour meter, battery charge level indicator, empty water tank level indicator and forward/reverse traction indicator. Speed control adjustment, horn, suction motor



switch with delayed switch-off, brush plate lifting/lowering selector switch, brush motor switch. All motors are protected by thermal breakers. The detergent water tank serves as battery compartment, allowing the housing of great capacity batteries. Battery charger and suction motor are placed the recovery tank; the housing of the

vacuum motor allows to drastically reduce the operating noise. The ergonomic and comfortable shape of the machine allows the operator to work effortless for a long time, improving productivity. Thanks to the compact dimensions the machine can work with agility even in narrow spaces.



OPTIONAL



- 4 x 0.107.0004
Tubular battery Pb-acid
6V 180Ah C5



- 4 x 0.107.0072
GEL Battery 6 MFP 180
6V 180Ah C5



- 0.108.0080
Battery Charger 24V 30A
220-240/50-6




- 4.508.0901 Polyurethane
front blade L.925 TH.3 Sh.40
- 4.508.0900 Polyurethane
rear blade L.1015 TH.4 Sh.40
- 4.508.1251 Polyurethane
front blade L.1027 TH.3
- 4.508.1252 Polyurethane
rear blade L.1150 TH.4



- * • 2x 5.511.2219
Tynex brush Ø 360 mm-14"
- 2x 5.511.2220
PP 0,3 brush Ø 360 mm-14"
- 2x 5.511.2221
PES brush Ø 360 mm - 14"



- 2x 5.511.2229
Tynex brush Ø 430 mm-17"
- 2x 5.511.2230
PP 0,3 brush Ø 430 mm-17"
- 2x 5.511.2231
PES brush Ø 430 mm - 17"



- * • 2x 5.511.2252
EWU pad driver Ø 380 mm-15"
- 2x 5.511.2232
EWU pad driver Ø 430 mm-17"



- 6.508.0143 - Ø 380 mm -
15"- beige (5 pcs.)
- 6.508.0144 - Ø 380 mm -
15"- green (5 pcs.)
- 6.508.0141 - Ø 380 mm -
15"- black (5 pcs.)
- 6.508.0032 - Ø 430 mm -
17"- beige (5 pcs.)
- 6.508.0039 - Ø 430 mm -
17"- green (5 pcs.)
- 6.508.0046 - Ø 430 mm -
17"- black (5 pcs.)