

Easy-R















CHARACTERISTICS

- Suitable to work for the maintenance and deep cleaning of large areas (up to 2.200 m²) User friendly control panel: forward speed setting, scrubbing and vacuuming selectors, battery charge indicator, traction direction indicator, key main switch Large handle with traction driving lever for forward and backward directions Self levelling brush plate Cover removable without tools provided with self locking system Quick vacuum motor and filter inspection, without tools Detergent solution tank with large opening protected by quick locking cap
- Parking brake directly on the wheel Non-marking wheels Easy squeegee regulation without tools Movable shock-proof squeegee
- Hour meter and solenoid valve. Quick refilling system

TECHNICAL DATA

	Easy-R 55BT	Easy-R 66BT
code	37002-00093	37002-00101
power supply	24V	24V
scrubbing/squeegee width	550/800 mm	660/800 mm
max working capacity	2475 m²/h	2970 m²/h
solution tank capacity	67 l/17.70 gal	67 l/17.70 gal
recovery tank capacity	75-95 I/20.35-25 gal	75-95 I/20.35-25 gal
traction/traction motor	automatic/200W	automatic/200W
RPM/pressure on the brushes	150/45 kg/99.20 lbs	150/24 kg/52.91 lbs
brush motor power	600 W	600 W
detergent solution system	solenoid valve	solenoid valve
depression/vacuum motor	1280 mmH ₂ O/450W	1280 mmH ₂ O/450W
dimension (cm)/weight	135x56x102/100 kg	135x56x102/93 kg

PLUS



User friendly control panel. Speed adjustment selectors. General ON/ OFF and key switch, brush and vacuum motor switch. Thermal circuit breaker to protect vacuum motor and brush motor, battery level control, hour meter.



Easy access to battery and vacuum motor compartment, without using tools. Large tank capacity, at the top in the category (67 l). $2 \times 12V$ -118 Ah C5 batteries to grant long work autonomy, up to 3 hours.



Control lever for brush operation and detergent water outflow. Recovery tank drain hose. Quick fitting battery charger plug.



Heavy duty 15 mm steel monobloc brush plate. Great pressure on the floor for a deep cleaning even on the toughest dirt. Self levelling system. Solenoid valve to stop the detergent water outflow during the work interruptions.

STANDARD EQUIPMENT



Easy-R 55BT • 2 x 10002-08092 PP brush Ø 275 mm - 10"



Easy-R 66BT • 2 x 10002-08097 PP brush Ø 330 mm - 13"



- 00005-02298 Front squeegee blade L.830 mm Shore 40 Th. 2.5 mm
- 00005-02297 Rear squeegee blade L.870 mm Shore 40 Th. 3 mm

OPTIONAL



Tubular battery Pb-acid 12V 118Áh C5





•2x 10002-08093 Tynex brush Ø 275 mm-10" •2x 10002-08094 PP 0.3 brush Ø 275 mm-10" •2x 10002-08095 PES brush Ø 275 mm-10"



• 2 x 00055-00130 GEL Battery 12 MFP 105 12V 105Ah C5

• 2x 10002-08098

Tynex brush Ø 330 mm-13"

•2x 10002-08099

PP 0.3 brush Ø 330 mm-13"

•2x 10002-08100

PES brush Ø 330 mm-13"





• 00056-00065 Battery Charger 24V 13A 220-240/50-60

• 2x 10002-08096

EWU pad driver Ø 275mm-10"

• 2x 10002-08101

EWU pad driver Ø 330mm-13"



- 12A



• 10001-08511 On-board Battery charger kit - 24V



- 00005-02268 Polyurethane front blade L.830 TH. 3
- 00005-02267 Polyurethane rear blade L.870 TH. 4



(5 pcs package) • 10001-09927 - Ø 280 mm-11"- beige

- 10001-09928 Ø 280 mm-11"- green
- 10001-09929 Ø 280 mm-11"- black



- (5 pcs package) • 10001-09911 - Ø 340 mm-13"- beige
- 10001-09916 Ø 340 mm-13"- green • 10001-09921 - Ø 340 mm-13"- black