


Midi-R



MORE INFO



CHARACTERISTICS

- Capable to work for the maintenance and deep cleaning of large areas (up to 2.600 m²)
- User friendly control panel: forward speed setting, scrubbing and vacuuming selectors, battery charge indicator, traction direction indicator, key main switch
- Large handle with traction driving lever for forward and backward directions
- Self levelling brush plate
- Cover removable without tools
- Quick vacuum motor and filter inspection, without tools
- Detergent solution filter
- Detergent solution tank provided with large opening protected by quick locking cap.
- Quick refilling system

TECHNICAL DATA

	Midi-R 75BT
code	37003-00010
power supply	24V
scrubbing/squeegee width	750/900 mm
max working capacity	4275 m ² /h
solution tank capacity	88 l/23.25 gal
recovery tank capacity	91-95 l/24.04-25 gal
traction type/power	automatic/300 W
RPM - pressure on the brushes	150 - 48,5 kg/107.48 lbs
brush motor power	1000 W
detergent solution system	solenoid valve
depression/vacuum motor	1733 mmH ₂ O/550 W
dimension (cm)/weight	133x73x117/150 kg

PLUS



Easy access to battery and vacuum motor compartment, without using tools. Large capacity shock and acid proof polyethylene tanks (88 l) avoid frequent refilling and idle time. 4 x 6V - 180 Ah C5 batteries granting continuous working time up to 4-5 hours.



Adjustable speed ensures high precision in cleaning congested areas with obstacles. Intuitive controls reduce operator's training time. Safety thermal breakers prevent motor problems in case of overheating or operator's misuse.



Heavy duty V-shaped squeegee ensures perfect drying of every type of floor, even with large joints. Non-marking wheels avoid marks after the drying. Completely adjustable to fit any surface.










Strong mechanical control levers for heavy duty use. Large size drain hose for a fast emptying and a better cleaning of the recovery tank. Quick fitting battery charger plug.

STANDARD EQUIPMENT

 <ul style="list-style-type: none"> • 2 x 10002-08108 PP brush Ø 360 mm - 14" 	 <ul style="list-style-type: none"> • 00005-02240 Front squeegee blade L.925 mm Shore 40 Th. 3 mm • 00005-02237 Rear squeegee blade L.1015 mm Shore 30 Th. 4 mm 			
---	--	--	--	--

OPTIONAL

 <ul style="list-style-type: none"> • 4 x 00055-00013 Tubular battery Pb-acid 6V 180Ah C20 + 2 x 10002-07046 connection cable batteries 	 <ul style="list-style-type: none"> • 4 x 00055-00142 Gel battery 6 MFP 180 6V 180Ah C5 + 2 x 10002-07046 connection cable batteries 	 <ul style="list-style-type: none"> • 00056-00067 Battery Charger 24V 30A 115-240/50-60 Connection cable batteries 00056-00067 SB50-SB80: 10002-08044 	 <ul style="list-style-type: none"> • 10001-08512 On-board Battery charger kit - 24V - 25A 	 <ul style="list-style-type: none"> • 00005-02253 Polyurethane front blade L.925 TH.3 Sh.40 • 00005-02252 Polyurethane rear blade L.1015 TH.4 Sh.40
 <ul style="list-style-type: none"> • 2x 10002-08109 Tynex brush Ø 360 mm-14" • 2x 10002-08110 PP 0,3 brush Ø 360 mm-14" • 2x 10002-08111 PES brush Ø 360 mm - 14" 	 <ul style="list-style-type: none"> • 2x 10002-08107 EWU pad driver Ø 360 mm-14" 	 <p>(5 pcs package)</p> <ul style="list-style-type: none"> • 10001-09944 - Ø 380 mm-15"- beige • 10001-09945 - Ø 380 mm-15"- green • 10001-09942 - Ø 380 mm-15"- black 		