



Motion 60BT**CHARACTERISTICS**

• Especially suitable for thorough cleaning of medium and large surfaces • Control panel with operator presence safety system • Low level battery indicator with brush/vacuum and traction progressive cut off • Solution water filter and solenoid valve • Easy access to the battery compartment • Quick drain and easily inspectable recovery tank • Non-marking wheels • Shock and acid resistant roto-molded polyethylene tanks • The lower tank is also battery compartment • Low noise operation thanks to the protected positioning of vacuum motor • Separate chemist (optional) • Possibility to mount Li-ion batteries • Accessory storage facility on request • Automatic lifting of the brush plate • With interchangeable brush head • **Adjustable brush pressure till 40 kg (continuous duty)** • FMS (Fleet Management System) available on request

Available also full optional version: gel batteries, battery charger, detergent dosing kit, water stop system and hook kit
MOTION 60 BT code 37036-00015

TECHNICAL DATA

	Motion 60BT	Motion 60BT	Motion 60BT	Motion 60BT
code	37036-00002	37036-00004	37036-00013	37036-00014
power supply	24 V	24 V (battery charger included)	24 V (battery charger included)	24 V (battery and charger included)
scrubbing/squeegee width	600/855 mm	600/855 mm	600/855 mm	600/855 mm
max working capacity	3200 m ² /h	3200 m ² /h	3200 m ² /h	3200 m ² /h
solution tank capacity	70 l/18.4 gal	70 l/18.4 gal	70 l/18.4 gal	70 l/18.4 gal
recovery tank capacity	83 l/21.9 gal	83 l/21.9 gal	83 l/21.9 gal	83 l/21.9 gal
traction	automatic/180W	automatic/180W	automatic/180W	automatic/180W
RPM/pressure on the brushes	150/40 kg / 88 lbs	150/40 kg / 88 lbs	150/40 kg / 88 lbs	150/40 kg / 88 lbs
brush motor power	2x400W	2x400W	2x400W	2x400W
detergent solution system	solenoid valve	solenoid valve	solenoid valve + dosing kit	solenoid valve
depression/vacuum motor	1200 mmH ₂ O/400W	1200 mmH ₂ O/400W	1200 mmH ₂ O/400W	1200 mmH ₂ O/400W
dimension (cm)/weight	134x81x116/125 kg	134x81x116/127 kg	134x81x116/129 kg	134x81x116/185 kg

PLUS


Interchangeable heads with orbital function and roller brush



Large and easily inspectable rotomolded polyethylene tank, shock and acid resistant



Equipped with an actuator for automatic brush plate activation and adjustable brush pressure continue 40Kg/88 lbs



Chemical dispenser tank (optional) standard on model code: 37036-00013 and 37036-00015 Motion 60BT

STANDARD EQUIPMENT

 • 2 x 10002-16258 PP brush Ø 305 mm - 12"	 • 00005-02293 Front squeegee blade L.960X57mm Th. 2,5mm • 00005-02292 Rear squeegee blade L.1000X57mm Th.3mm	 • 1 x 00056-00062 On-board Battery charger 24V 10A 100-240V 50-60Hz Only model cod. 37036-00004/37036-00013/37036-00014/37036-00015	 • 2 x 00055-00130 Gel Battery 12V 105A/C5-120A/C20 Only model cod. 37036-00014/37036-00015	 • 00014-01349 Refill hose 1,7m
---	---	---	--	--

OPTIONAL

 • 2 x 00055-00149 Tubular battery Pb-acid 12V 118Ah C5	 • 2 x 00055-00130 Gel Battery 12V 105A/C5-120A/C20	 • 2 x 00055-00181 Cyclic AGM battery 12V 136Ah C5-150Ah C2	 • 00005-02633 Polyurethane front blade L.960 TH.2,5 Sh.40 • 00005-02632 Polyurethane rear blade L.1000 TH.3 Sh.40	 • 2 x 10002-16259 Tynex brush Ø 305 mm-12" • 2 x 10002-16260 PP brush Ø 305 mm-12" • 2 x 10002-16261 PES brush Ø 305 mm-12"
 • 2 x 10002-16262 x2 EWU pad driver Ø 305 mm - 12"	 • 10001-14034 - Ø 305 mm-12" - beige • 10001-14035 - Ø 305 mm-12" - green • 10001-13262 - Ø 305 mm-12" - black	 • 10001-12852 accessory hook kit		