

Sprinter











CHARACTERISTICS

Suitable to work in high congested areas like small shops, offices, kitchens, schools, hospitals, bars, gyms, restaurants
Three controls for brush drive, washing and drying operations
Double floor squeegee for both forward and reverse drying
Sound pressure 68 dB (A)
Min. working height required 200 mm
Structure built with durable materials
Suitable load on the brush for an optimal cleaning


efficiency • Detachable detergent/recovery tank • Cable holder • 7mt electric cable • Non-marking wheels.

TECHNICAL DATA

	Sprinter
code	37021-00002
power supply	230 V - 50 Hz
scrubbing/squeegee width	290/320 mm
max working capacity	1015 m²/h
solution tank capacity	2.8 I/0.74 gal
recovery tank capacity	5.6 l/1.48 gal
traction	mechanical
RPM/pressure on the brush	1000/7 kg/15,43 lbs
brush motor power	200 W
noise level dB (A)	68
depression/vacuum motor	1428 mmH ₂ O/800 W
dimension (cm)/weight	37 x 37 x 113/13 kg

WALK BEHIND

PLUS



- 1) Brush motor
- 2) Vacuum motor
- 3) Detergent solution flow
- 4) Dirty liquid flow



Double squeegee for both forward and reverse washing and drying. PP brush suitable for most common floors (brush for carpet and moquette cleaning available cod. 10001-09817). ABS shock-proof covers. Non-marking rubber wheels.



Minimun working height 200 mm, allowing perfect cleaning under furnitures, chairs, tables, beds, etc. The tilting handle makes easy and stressless the daily use of the machine.Large tank capacity avoiding frequent refilling of the unit



Cylindrical brush quick connection and release: the fitting and releasing of the brush does not require the use of tools. Ordinary cleaning and maintenance are simple and quick for anybody

STANDARD EQUIPMENT







Stationary plate



OPTIONAL



