

## SWL R 1100 Bin-Up

### STANDARD EQUIPMENT



**ELECTRIC  
FILTER SHAKER**



POWERED by  
**HONDA**

-  0.961.0176  
PP SWL R 1100 ET
-  0.961.0178  
PP-Mixed steel SWL R  
1100 DT/ST/GT
-  2 x 0.961.0177  
PP SWL R 1100 ET
-  2 x 0.961.0179  
PP-Mixed steel SWL R  
1100 DT/ST/GT
-  8 x 0.961.0020  
paper filter 20 µm

Optional:

- 0.961.0020 polyester filter
- 0.961.0180 Hepa filter
- Battery (model ET):
  - 4 x 0.107.0080 tubular battery pb-acid  
- 6V 320 Ah C5  
+ 3 x 5.511.0561  
+ 1x 5.511.2190
- Battery charger (model ET):
  - 0.108.0082 - 24V-60A 230V 50-60 Hz

Available models with limiting gradient 20%

SWL R 1100 DT BIN-UP cod. 0.061.0057

SWL R 1100 ST BIN-UP cod. 0.061.0059

### Equipped with:

- Large filter surface distributed on 8 cartridge filters fitted with electric filter shaker.
- Side brush raising control.
- **Complete right/left side brush.**
- Anti-trace wheels (mod.ET).
- 2 m steering angle and lift flap pedal.
- Main brush pressure regulation.
- Service and parking brake.
- Hour meter and klaxon and flashing light.
- Indirect back collection.
- Front dust vacuum system.
- Quick changing of the main brush and side brush without tools.
- Long life elastic belts.
- Suction selection lever.
- Antistatic device.
- Battery level indicator (mod.ET).
- 115 lt wide collector tank.
- Dumping height, hydraulic lift 1450 mm
- Heavy duty steel frame.
- Adjustable seat.
- Battery and battery charger not included.
- 24V - 1200W AC three-phase traction motor
- **Front working light system.**

	SWL R 1100 ET BIN-UP	SWL R 1100 DT BIN-UP	SWL R 1100 ST BIN-UP
code	0.061.0043	0.061.0041	0.061.0045
main brush width	800mm / 31,50 inc	800mm / 31,50 inc	800mm / 31,50 inc
main brush + 1 side brush	1050mm / 41,34 inc	1050mm / 41,34 inc	1050mm / 41,34 inc
main brush + 2 side brushes	1300mm / 51,19 inc	1300mm / 51,19 inc	1300mm / 51,19 inc
collector tank	115 lt / 30,3 gal	115 lt / 30,3 gal	115 lt / 30,3 gal
max working capacity	9700 m <sup>2</sup> /h-104409 ft <sup>2</sup> /h	9700 m <sup>2</sup> /h-104409 ft <sup>2</sup> /h	9700 m <sup>2</sup> /h-104409 ft <sup>2</sup> /h
traction / limiting gradient	front wheels / 20%	front wheel / 10%	front wheel / 10%
max speed	7,5 km/h-4,66 mile/h	7,5 km/h-4,66 mile/h	7,5 km/h-4,66 mile/h
motor type / power	24V/3,47 kW	Diesel Yanmar 6,7 Hp/4,92 kW	Honda 6,5 Hp/4,88 kW
filtering surface	6,4 m <sup>2</sup> / 68,89 ft <sup>2</sup>	6,4 m <sup>2</sup> / 68,89 ft <sup>2</sup>	6,4 m <sup>2</sup> / 68,89 ft <sup>2</sup>
filter shaker	electric	electric	electric
dimension / weight	160x101x130 cm/448 kg	160x101x130 cm/454 kg	160x101x130 cm/434 kg